

EL-218-30K-WH 2 in. LED Round Adjustable Downlight

SPECIFICATION SHEET



SPECIFICATIONS

Brightness: 680 Lumens Power (Watts): 9 Watt Voltage: 120V AC LED CCT: 3000K Beam Angle: 36° CRI: 90 +

Dimmable: Yes, Triac/ELV


Environment: Wet or Dry Location **Dimensions:** 3.125 in D x 1.625 in H

Finish: White Manufacturer: Elumalight

Energy Star, cULus Wet Listed, CEC Title 24, Meets ASTM-E283 Airtight Requirements Rating:

± 30,000 - 50,000 hours Avg. Lifetime:

Warranty: 5 Year Limited



JOB NAME:

LOCATION:

QUOTE/REF#:

DESCRIPTION

The 2 in. LED Round Adjustable Trim is suitable for use with a 2 in. recessed housing. It produces even illumination without diode image and swivels up to a 25° angle. Suitable for use in fixtures installed in insulated ceilings, new construction, remodel housings, and 2 in. recessed fixtures installations with 2-wire connector.

The low profile unit is CA Title 24 compliant, meets ENERGY STAR requirements, and UL wet listed. It produces 650 lumens at 90+ CRI. Available in Warm White 3000K.

KEY FEATURES

- Easy to Install
- **Even Lighting Illumination**
- Low-heat dissipation
- Long lifespan 50000 hours
- **Energy Star Listed**
- cULus Wet Listed
- CEC Title 24 Listed
- Meets ASTM-E283 Air Tight requirements

APPLICATIONS

- **LED Bathroom Lighting**
- Residential Ceiling Down Lighting
- Commercial Ceiling Down Lighting
- Living Room Lighting
- Office Lighting
- LED Kitchen Lighting
- Pot Lights













