

# **EL-24VM-RGB** LED RGB Mini Flex Neon Lights

JOB NAME:

LOCATION: QUOTE/REF#:

# SPECIFICATION SHEET



### SPECIFICATIONS

**Brightness:** 400 Lumens/ft

1312 Lumens/meter

Power (Watts): 4 watt/ft

120 watt/30ft roll

Input Voltage: 24V DC **LED Color: RGB** IP Rating: **IP65** 

**Environment: Outdoor Wet Location** 

Beam Angle: 120° Length: 30 ft roll

Width: 0.23 in / 6 mm wide 0.47 in / 12 mm thick **Height:** 

Cut Increment: 2 in / 50.8 mm at cut marking **EL-12VM-CLIP Mounting Clip** Mounting:

EL-12VM-CH Channel

(sold separately)

Manufacturer: Elumalight Rating: UL, ETL, RoHS

Avg. Lifetime: ± 30,000 - 50,000 hours

Warranty: 3 years limited

# **DESCRIPTION**

This durable LED RGB Mini Flex Neon Light is an ideal way to add a decorative touch to any space. It's 24V DC and 30 Ft long and features a bright color illumination to bring any area to life. Easy to install and maintain, it's perfect for those looking to quickly and easily create a unique atmosphere

The 24V DC RGB Mini Flex Neon can also be mounted into an aluminum profile channel or silicone into place. Mounting on the side of a display or cabinet can be done with regular 3M Double-faced Tape or Carpet Tape making this a simple onsite installation.

#### **KEY FEATURES**

- Flexible, Durable, & Easy to Install
- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- SMD 5050 RGB LEDs Chipsets are high-intensity, ultra-bright, and energy-efficient
- No RF interference
- Up to 50,000 hours of Lifespan
- Dimmable with compatible dimmer and power supply
- Rated IP65 for Wet Locations
- **UL Listed, RoHS Compliant**

## **APPLICATIONS**

- **Custom Signage**
- Tradeshows Exhibits, Retail Displays
- Accent and decorative lighting
- Architectural lighting for corridors, canopies, archways, or windows
- **Downlighting or Uplighting Applications**
- Backlighting or edge-lighting
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects









