

## SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



## DESCRIPTION

The 3 in. LED Round Gimbal downlight insert is engineered with energy-efficient LED technology that produces even illumination with an incredible 93+ CRI. Designed to be used for New Construction, Remodel, and Retrofit applications, these inserts are rated for a life up to 50,000 hours, and meet the Title 24 and Energy Star requirements. Suitable for IC and Non-IC housings.

The best choice for simple exhibit and display lighting projects. It produces even illumination without diode image. The low profile unit is CA Title 24 compliant, meets ENERGY STAR requirements, and UL wet listed. It produces 700 lumens.

## SPECIFICATIONS

<b>Brightness:</b>	700 Lumen
<b>Power:</b>	9 Watt
<b>Voltage:</b>	120V AC
<b>LED CCT:</b>	3000K
<b>CRI:</b>	93+
<b>Dimmable:</b>	Yes, Triac/ELV
<b>Environment:</b>	Wet or Dry Location
<b>Aperture:</b>	3 in
<b>Dimensions:</b>	4.375 in D x 2.06 in H
<b>Finish:</b>	White
<b>Manufacturer:</b>	Elumalight
<b>Rating:</b>	Energy Star, cULus Wet Listed, CEC Title 24, Meets ASTM-E283 Airtight Requirements
<b>Avg. Lifetime:</b>	± 30,000 - 50,000 hours
<b>Warranty:</b>	5 Year Limited

## KEY FEATURES

- Easy to Install
- Even Lighting Illumination
- Low-heat dissipation
- Die-Cast construction provides lasting durability
- 25° tilt, 358° rotation
- CA Title 24, ENERGY STAR®, JA8-2016-E
- Life Span of 50,000 hours L70

## APPLICATIONS

- LED Bathroom Lighting
- Residential Ceiling Down Lighting
- Commercial Ceiling Down Lighting
- Living Room Lighting
- Office Lighting
- LED Kitchen Lighting
- Pot Lights

