

SPECIFICATION SHEET

SPECIFICATIONS

Brightness:	280 Lumens		
Power:	3.5 Watt		
Input Voltage:	12V DC		
LED CCT:	3000K or 6000K		
IP Rating:	IP20		
Environment:	Indoor Use - Dry Location		
Dimmable:	Yes, if used with Dimmable Driver		
Beam Angle:	120°		
LED Density:	3 LED per Fixture		
Cut-out:	2.28 in / 57.91 mm diameter		
Diameter:	2.72 in / 69.09 mm		
Depth:	0.8 in / 20.32 mm		
Finish:	White, Satin Nickel,		
Mounting:	Recessed or Surface Mount		
Manufacturer:	Elumalight		
Rating:	UL, ETL Listed		
Avg. Lifetime:	± 30,000 - 50,000 hours		
-			

* Required: The LED Puck Light 3.5w requires 12V DC LED Driver and optional Extension Cords. Sold separately.

EL-315 LED Puck Lights 3.5 Watt

JOB NAME:

10	CA	AI.
		 IN .

QUOTE/REF#:

DESCRIPTION

The 12V DC 3.5 Watt LED Round Puck Light is bright, ultra-low profile, and low power consumption. It is the perfect light source for any retail display, exhibit, commercial, or residential lighting applications.

Our LED Round puck lights are popular due to the low pro-file design and versatility to fit into small spaces and provide smooth lighting to under cabinet, under shelves, retail display cases, or general lighting applications.

Available in Satin Nickel or White finish in 6000K Cool White or 3000K Warm White Color Temperature options.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- No IR or UV radiation .
- Suitable for flat ceilings, sloped ceiling, or under-cabinet installations
- Easy to mounting and install
- LEDs Chipsets are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Long lifespan: Up to 50,000 hours

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways,
- Downlighting or Uplighting Recessed Applications
- Gallery and Museum Lighting
- Under-cabinet, Under-Counter, or accent lighting



© 2020 Step 1 Dezigns, Inc. All Rights Reserved. Specifications are subject to change without notice.