

SPECIFICATION SHEET

PRODUCT # : EL-324-BK/BR

Fixture Specifications:

- Housing:** Die-cast aluminum
- Finish :** Polyester UV powder coated, in **BK-Black**. Also available in **BR- Natural Brass**.
- Lens:** Clear, tempered and heat resistant convex glass. Extra flat lens included.
- Socket:** Top grade ceramic bi-pin socket with retention clip.
- Lamp:** 12V, MR-16, 50W max. Available in LED (3.5W & 5W) or without lamp. See the Lamp Guide below for more information.
- Gasket:** Silicone "O" ring seals faceplate to housing providing weather tight protection.

•Well Lights

•Aluminum

- Wiring:** Fixture is prewired with a 3ft 18-2 SJT-W directburial cord. Wire connector sold separately. Silicone filled wire nut (**CX-854**) or quick-locking wire connector (**CX-LOC**) is available from Step 1 Dezigns.
- Mounting:** In-ground direct burial or concrete encasement.
- Electrical Notes:** A remote 12V transformer is required. Options are available. Voltage range for LED lamps are 9V-17V. Proper grease/lubricant is suggested on threaded parts during installation process.
- Warranty:** Limited one (1) year warranty on aluminum fixture against manufacturer's defects.

