

EL-44130W | EL-44230W

4 in. LED Square Downlights

SPECIFICATION SHEET





SPECIFICATIONS

Brightness: 700 Lumen Power: 10 Watt Voltage: 120V AC 3000K LED CCT: **Beam Angle:** 90° 90+ CRI:

Dimmable: Yes, with compatible dimmer

Environment: Wet or Dry Location Length: 4.875 in / 123.83 mm Width: 4.875 in / 123.83 mm Height: 2.5 in / 63.5 mm Finish: White or Bronze Trims: Baffle or Reflector

Manufacturer: Elumalight

Energy Star, cULus Wet Listed, CEC Title 24, Meets ASTM-E283 Airtight Requirements Rating:

Avg. Lifetime: ± 30,000 - 50,000 hours

Warranty: 5 Year Limited

Product SKU	Finish	Trim
EL-44130W-30K-WH	White	Baffle
EL-44130W-30K-BZ	Bronze	Baffle
EL-44230W-30K-WH	White	Reflector
EL-44230W-30K-BZ	Bronze	Reflector

JOB NAME:

LOCATION: QUOTE/REF#:

DESCRIPTION

The 4 in. LED Square Downlights are engineered with energy-efficient LED technology that produces even illumination with an incredible 90+ CRI. Designed to be used for New Construction, Remodel, and Retrofit applications, these inserts are rated for a life up to 50,000 hours, and meet the Title 24 and Energy Star requirements. Suitable for IC and Non-IC housings. The best choice for simple exhibit and display lighting projects.

KEY FEATURES

- Easy to Install
- **Even Lighting Illumination**
- Low-heat dissipation
- Long lifespan 50000 hours
- **Energy Star Listed**
- cULus Wet Listed
- CEC Title 24 Listed
- Meets ASTM-E283 Air Tight requirements
- Suitable for use in fixtures installed in insulated ceilings.
- Suitable for installation in tall and shallow cans.
- Suitable for new construction and remodel housings.
- Suitable for installation into a 4" recessed fixtures with 2-wire connector.
- Suitable for installation into a 4" recessed fixtures with medium base socket, using an adaptor (included).

APPLICATIONS

- LED Bathroom Lighting
- Residential Ceiling Down Lighting
- Commercial Ceiling Down Lighting
- Living Room Lighting
- Office Lighting
- LED Kitchen Lighting
- Pot Lights











