

EL-4840XS-CCT | EL-9660XS-CCT

LED CCT Dimmable Covered Slim Strip Lights

SPECIFICATION SHEET



SPECIFICATIONS

Brightness: 4400 Lumens (4 Ft EL-4840XS-CCT)

6600 Lumens (8 Ft EL-9660XS-CCT)

Power: 40 watt (4 Ft)

60 watt (8 Ft)

Input Voltage: 120/277V AC

LED CCT: 3000K, 4000K, 5000K Multi-CCT Switchable

Beam Angle: 127.9° **CRI:** 80+

Dimmable: 10% 0-10V

IP Rating: IP20

Environment: Dry Locations

Dimensions: 48 in L x 0.87 in W x 2.48 in H (**EL-4840XS-CCT**)

96 in L x 0.87 in W x 2.48 in H (EL-9660XS-CCT)

Mounting: Surface mounting for ceiling or wall

mounting, compatible with most

ceiling types.

Finish: White

Manufacturer: Elumalight

Rating: cETLus Listed

Avg. Lifetime: ± 30,000 - 50,000 hours

Warranty: 5 Year Limited

JOB NAME: LOCATION: QUOTE/REF#:

DESCRIPTION

The new LED CCT Dimmable Covered Slim Strip Lights has a covered lens providing an even light distribution. Its slimline profile allows it to be undetected when mounted to the ceiling. Available in 4 ft or 8 ft length options.

KEY FEATURES

- Operates on 120-220V AC
- Multi CCT Switchable 3000K, 4000K, 5000K
- 0-10V Dimmable
- Post painted body
- Rectangular easy fit polycarbonate lens
- 50000 hours lifespan, 3-year warranty
- Mounting hardware & j-box cover included

APPLICATIONS

- Garages
- Carports
- Walkways
- Warehouse
- Retail Stores
- Restrooms
- Commercial Buildings
- Offices









