

SPECIFICATION SHEET

JOB NAME: _____

LOCATION: _____

QUOTE/REF#: _____



DESCRIPTION

Step 1 Designs LED 2x2 backlit LED panel with Multi-Watt selection and Multi-CCT selection. The wattage and color temperature can be changed via dip switches. It is ideal for any office, retail, healthcare, or educational environment. It replaces Fluorescent Troffer with integrated dimmable capability.

SPECIFICATIONS

Power (Watts):	20/25/30/35 watts (60 Hz)
Input Voltage:	120-277V AC
Brightness:	2500/3125/3750/4375 Lumen
LED CCT:	Selectable 3000/3500/4000/5000K
Dimmable:	Yes 10% 0-10V
IP Rating:	IP20
Environment:	Dry Location
Beam Angle:	114°
Fixture Length:	23.74 in
Fixture Width:	23.74 in
Fixture Height:	1.38 in
Mounting:	T-Bar Drop Ceiling, or Surface Mount Frame Kit (Sold Separately)
Finish:	Acrylic Diffuser in White Finish Frame
Manufacturer:	Elumalight
Rating:	UL, DLC
Avg. Lifetime:	± 30,000 - 50,000 hours
Warranty:	5 years limited

KEY FEATURES

- Instant On LED
- Multi-Watt Adjustable Switch
- Multi CCT Color Adjustable
- Even & Smooth Lighting Distributing Light Lens
- Replaces 2x2 Fluorescent Troffers
- A junction Box Included for Easy Connections
- 10% 0-10V Dimming
- Long lifespan 50000 hours

