

## SPECIFICATION SHEET

JOB NAME: \_\_\_\_\_

LOCATION: \_\_\_\_\_

QUOTE/REF#: \_\_\_\_\_



## DESCRIPTION

Step 1 Designs LED 2x4 backlit LED panel with Multi-Watt selection and Multi-CCT selection. The wattage and color temperature can be changed via dip switches. It is ideal for any office, retail, healthcare, or educational environment. It replaces Fluorescent Troffer with integrated dimmable capability.

## SPECIFICATIONS

<b>Power (Watts):</b>	35/40/45/50 watts (60 Hz)
<b>Input Voltage:</b>	120-277V AC
<b>Brightness:</b>	4375/5000/5625/6250 Lumen
<b>LED CCT:</b>	Selectable 3000/3500/4000/5000K
<b>Dimmable:</b>	Yes 10% 0-10V
<b>IP Rating:</b>	IP20
<b>Environment:</b>	Dry Location
<b>Beam Angle:</b>	114°
<b>Fixture Length:</b>	47.75 in
<b>Fixture Width:</b>	23.74 in
<b>Fixture Height:</b>	1.18 in
<b>Mounting:</b>	T-Bar Drop Ceiling, or Surface Mount Frame Kit (Sold Separately)
<b>Finish:</b>	Acrylic Diffuser in White Finish Frame
<b>Manufacturer:</b>	Elumalight
<b>Rating:</b>	UL, DLC
<b>Avg. Lifetime:</b>	± 30,000 - 50,000 hours
<b>Warranty:</b>	5 years limited

## KEY FEATURES

- Instant On LED
- Multi-Watt Adjustable Switch
- Multi CCT Color Adjustable
- Even & Smooth Lighting Distributing Light Lens
- Replaces 2x4 Fluorescent Troffers
- A junction Box Included for Easy Connections
- 10% 0-10V Dimming
- Long lifespan 50000 hours

