

EL-610SDW | EL-610SDBZ

5 or 6 in. LED Dims to Warm Round Baffle Downlights

SPECIFICATION SHEET





SPECIFICATIONS

Brightness: 700 Lumen Power: 10 Watt Voltage: 120V AC

Dims to Warm 3000K-1800K LED CCT:

Beam Angle: 90° CRI: 90+

Dimmable: Yes, Triac/ELV **Environment:** Dry or Wet Location Aperture: 4.875 in / 123.83 mm Diameter: 7.5 in / 190.5 mm Height: 3 in / 76.2 mm

Trim: Baffle

White EL-610SDW Finish:

Bronze **EL-610SDBZ**

Manufacturer: Elumalight


Rating: UL Listed for Wet Location. RoHS

Compliant. ENERGY STAR® Certified.

California Title 24 JA8-2016-E.

± 30,000 - 50,000 hours Avg. Lifetime:

Warranty: 5 Year Limited



JOB NAME: LOCATION: QUOTE/REF#:

DESCRIPTION

Step 1 Dezigns 5 or 6 in. LED Dims to Warm Round Downlights are engineered with energy-efficient LED technology that produces even illumination with an incredible 90+ CRI. Designed to be used for New Construction, Remodel, and Retrofit applications, these inserts are rated for a life of 50,000 hours, and meet the Title 24 and Energy Star requirements. Suitable for IC and Non-IC housings.

KEY FEATURES

- Dims from a bright 3000K to a warm 1800K
- Fits 5" or 6" Dedicated LED Recessed Housings, Regular and Shallow
- Includes Medium Base Adapter for retrofitting existing E26 Base housings
- Soft white lens provides smooth lumen distribution and eliminates LED pixelation
- Deep set LED trim reduces glare while providing area
- CA Title 24, ENERGY STAR, JA8-2016-E
- Life Span of 50,000 hours L70

APPLICATIONS

- **LED Bathroom Lighting**
- Residential Ceiling Down Lighting
- Commercial Ceiling Down Lighting
- Living Room Lighting
- Office Lighting
- Home Theater LED Lights
- LED Kitchen Lighting
- Pot Lights















630 Terminal Way, Costa Mesa, CA 92627



EL-615SDW | EL-615SDBZ

5 or 6 in. LED Dims to Warm Round Reflector Downlights

SPECIFICATION SHEET





SPECIFICATIONS

Brightness: 700 Lumen Power: 10 Watt Voltage: 120V AC

Dims to Warm 3000K-1800K LED CCT:

Beam Angle: 90° CRI: 90+

Dimmable: Yes, Triac/ELV **Environment:** Dry or Wet Location Aperture: 4.875 in / 123.83 mm Diameter: 7.5 in / 190.5 mm Height: 3 in / 76.2 mm Trim: Reflector

White EL-615SDW Finish:

Bronze **EL-615SDBZ**

Manufacturer: Elumalight


Rating: UL Listed for Wet Location. RoHS

Compliant. ENERGY STAR® Certified.

California Title 24 JA8-2016-E.

± 30,000 - 50,000 hours Avg. Lifetime:

Warranty: 5 Year Limited



JOB NAME: LOCATION: QUOTE/REF#:

DESCRIPTION

Step 1 Dezigns 5 or 6 in. LED Dims to Warm Round Downlights are engineered with energy-efficient LED technology that produces even illumination with an incredible 90+ CRI. Designed to be used for New Construction, Remodel, and Retrofit applications, these inserts are rated for a life of 50,000 hours, and meet the Title 24 and Energy Star requirements. Suitable for IC and Non-IC housings.

KEY FEATURES

- Dims from a bright 3000K to a warm 1800K
- Fits 5" or 6" Dedicated LED Recessed Housings, Regular and Shallow
- Includes Medium Base Adapter for retrofitting existing E26 Base housings
- Soft white lens provides smooth lumen distribution and eliminates LED pixelation
- Deep set LED trim reduces glare while providing area illumination.
- CA Title 24, ENERGY STAR, JA8-2016-E
- Life Span of 50,000 hours L70

APPLICATIONS

- **LED Bathroom Lighting**
- Residential Ceiling Down Lighting
- Commercial Ceiling Down Lighting
- Living Room Lighting
- Office Lighting
- Home Theater LED Lights
- LED Kitchen Lighting
- Pot Lights















630 Terminal Way, Costa Mesa, CA 92627