

### SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



### DESCRIPTION

6 in LED Retrofit Reflector Trim is cULus listed for use in existing IC or Non-IC housings. The fixture provides 1000 Lumen output, drawing 16.6W and rendering 95 CRI.

The LEDs integrate the latest LED technology, giving bright spectacular light output and low power consumption. An obvious and smart choice for Green Energy efficient lighting in commercial and residential lighting applications.

### SPECIFICATIONS

<b>Brightness:</b>	1000 Lumen
<b>Power:</b>	16.6 Watt
<b>Voltage:</b>	120V AC
<b>LED CCT:</b>	2700K, 3000K, or 4000K
<b>Beam Angle:</b>	120°
<b>CRI:</b>	90+
<b>Dimmable:</b>	Yes, with compatible dimmer
<b>Environment:</b>	Wet or Dry Location
<b>Aperture:</b>	6 in / 152.4 mm
<b>Diameter:</b>	7.625 in / 193.68 mm
<b>Height:</b>	4 in / 101.6 mm
<b>Included:</b>	Medium base socket adapter for easy retrofitting in 6" recessed housing
<b>Finish:</b>	White, Bronze, Diffused Clear / White, Haze / White
<b>Manufacturer:</b>	Elumalight
<b>Rating:</b>	Energy Star, cULus Wet Listed, CEC Title 24, Meets ASTM-E283 Airtight Requirements
<b>Avg. Lifetime:</b>	± 30,000 - 50,000 hours
<b>Warranty:</b>	5 Year Limited

### KEY FEATURES

- Easy to Install
- Even Lighting Illumination
- Low-heat dissipation
- Long lifespan 50000 hours
- Energy Star Listed
- cULus Wet Listed
- CEC Title 24 Listed

### APPLICATIONS

- LED Bathroom Lighting
- Residential Ceiling Down Lighting
- Commercial Ceiling Down Lighting
- Living Room Lighting
- Office Lighting
- LED Kitchen Lighting
- Pot Lights

### MOUNTING

- Recessed mount into 6" housing. A quick connector is compatible with most dedicated LED housings. Required by some codes in recessed can applications or to meet energy rebate program requirements.

