

SPECIFICATION SHEET



JOB NAME:

LOCATION:

QUOTE/REF#:

SPECIFICATIONS

Incandescent Equiv:	120 Watts (18 watts) 150 Watts (22 watts) 200 Watts (36 watts)
Fluorescent Equiv:	32 Watts (18 watts) 40 Watts (22 watts) 55 Watts (36 watts)
HID Equivalent:	70 Watts (18 watts) 100 Watts (22 watts) 150 Watts (36 watts)
Input Voltage:	120-277V AC
Shape:	Corn cob
Base	Medium
ANSI Base	E26
Finish	White, Un-Lensed
LED CCT	5000K
CRI	80+
Beam Spread:	300°
Dimmable:	Non-Dimmable
Ballasting:	Ballast by-pass - Direct wire only 100-277V
Manufacturer:	Elumalight
Rating:	IP64 Damp Location
Labels:	cULus, RoHS, FCC,
Avg. Lifetime	± 50,000 hours
Warranty	5 years limited

DESCRIPTION

E26 Medium Base LED Retrofit Corn Light Bulbs are designed to replace HID lamps. It is a great alternative that will help you save on utility costs. Step 1 Dezigns LED corn light bulb lasts longer than traditional HID or Metal Halide Lamps, so you save money on costs of replacement.

These LED retrofits illuminate the same amount of light output of their HID light bulb equivalent. Moreover, LED corn cob lamps maintain a bright light throughout their lifespan. These LED corn light bulbs are ideal for applications such as parking lot, post top and warehouse high bay light fixtures.

LED Corn Light Bulbs are great for multiple applications that require metal halide or HID lighting replacement, this LED corn light bulb is the perfect fit when you are seeking an LED HID retrofit lamp for bollards, post tops, or replacement for traditional energy-draining warehouse lights.

KEY FEATURES

- High Lumen Omni-directional LED for Industrial or Commercial applications
- Replaces HID, CFL, and Incandescent
- Built-in surge protection
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP64 rated
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)

ORDER SKUS

Product SKU	Wattage	Brightness	Dimensions
EL-CLBE26-18W-50K	18W	2160 Lumens	5.69 in MOL x 2.38 in MOD
EL-CLBE26-22W-50K	22W	3080 Lumens	5.69 in MOL x 2.38 in MOD
EL-CLBE26-36W-50K	36W	5148 Lumens	7.34 in MOL x 3.34 in MOD

