

SPECIFICATION SHEET



JOB NAME: _____

LOCATION: _____

QUOTE/REF#: _____

SPECIFICATIONS

- Incandescent Equiv:** 300 Watts (45 watts)
400 Watts (80 watts)
500 Watts (100 watts)
- Fluorescent Equiv:** 65 Watts (45 watts)
100 Watts (80 watts)
150 Watts (100 watts)
- HID Equivalent:** 175 Watts (45 watts)
320 Watts (80 watts)
400 Watts (100 watts)
- Input Voltage:** 120-277V AC
- Shape:** Corncob
- Base:** Mogul Extended
- ANSI Base:** EX39
- Finish:** White, Un-Lensed
- LED CCT:** 5000K
- CRI:** 80+
- Beam Spread:** 300°
- Dimmable:** Non-Dimmable
- Ballasting:** Ballast by-pass - Direct wire only 100-277V
- Manufacturer:** Elumalight
- Rating:** IP64 Damp Location
- Labels:** cULus, RoHS, FCC,
- Avg. Lifetime:** ± 50,000 hours
- Warranty:** 5 years limited

DESCRIPTION

EX39 Mogul Base LED Retrofit Corn Light Bulbs are designed to replace HID lamps. It is a great alternative that will help you save on utility costs. Step 1 Dezigns LED corn light bulb lasts longer than traditional HID or Metal Halide Lamps, so you save money on costs of replacement.

These LED retrofits illuminate the same amount of light output of their HID light bulb equivalent. Moreover, LED corn cob lamps maintain a bright light throughout their lifespan. These LED corn light bulbs are ideal for applications such as parking lot, post top and warehouse high bay light fixtures.

Step 1 Dezigns LED Corn Light Bulbs are great for multiple applications that require metal halide or HID lighting replacement, this LED corn light bulb is the perfect fit when you are seeking an LED HID retrofit lamp for bollards, post tops, or replacement for traditional energy-draining warehouse lights.

KEY FEATURES

- High Lumen Omni-directional LED for Industrial or Commercial applications
- Replaces HID, CFL, and Incandescent
- Built-in surge protection
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP64 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)

ORDER SKUS

Product SKU	Wattage	Brightness	Dimensions
EL-CLBEX39-45W-50K	45W	6435 Lumens	11 in L x 8 in W x 8 in D
EL-CLBEX39-80W-50K	80W	11440 Lumens	9.25 in L x 17.32 in W x 9.25 in D
EL-CLBEX39-100W-50K	100W	14300 Lumens	17.32 in L x 9.25 in W x 9.25 in D

