

SPECIFICATION SHEET

JOB NAME: _____

LOCATION: _____

QUOTE/REF#: _____



SPECIFICATIONS

- Brightness:** 320 Lumens/ft
1050 Lumens/meter
- Power (Watts):** 3 watt/ft
9.84 watt/meter
- Input Voltage:** 5-24V DC
- LED Colors:** RGB (Red, Green, Blue)
- IP Rating:** IP65
- Environment:** Wet or Dry Location
- Beam Angle:** 120°
- LED Density:** 10 LEDs/ft
30 LEDs/reel
- LED Chip Size:** SMD 5050
- LED Spacing:** 0.83 in / 21.1 mm
- Length:** 3 ft / 1 meter long
- Width:** 0.39 in / 10 mm wide
- Height:** 0.07 in / 1.78 mm thick
- Cut Increment:** 1.25 in / 31.75 mm at cut marking
- Backing:** 3M Adhesive
- Manufacturer:** Elumalight
- Rating** UL, ETL, RoHS
- Avg. Lifetime** ± 30,000 - 50,000 hours
- Included:** 1 Reel of RGB Strip, 1 4-Pin Connector,
1 Controller, 1 Remote, 1 Battery Box
- Required:** AA Batteries Not Included

DESCRIPTION

The 5V-24V DC Battery Operated Color Changing LED RGB Tape Light Kit is made with commercial-grade PCBs to ensure a long lifespan and even illumination. It is the perfect lighting solution for tradeshows, exhibitions lighting, retail display lighting, back-lighting, DIY lighting projects, and more. The LED RGB strip is rated IP65 for web locations.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- SMD 5050 RGB LED Chipsets are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Up to 50,000 hours Lifespan
- CE Listed, RoHS

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Backlighting or edge-lighting for sign letters
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects

