

**SPECIFICATION SHEET**

JOB NAME: \_\_\_\_\_

LOCATION: \_\_\_\_\_

QUOTE/REF#: \_\_\_\_\_



**SPECIFICATIONS**

- Brightness:** 480 Lumens/ft  
1574 Lumens/meter
- Power (Watts):** 3.2 watt/ft  
10.5 watt/meter
- Input Voltage:** 12V DC
- LED CCT:** 6000K Cool White
- CRI:** 90+
- IP Rating:** IP20
- Environment:** Indoor Use - Dry Location
- Beam Angle:** 120°
- LED Density:** 36 LEDs/ft  
600 LEDs/reel
- LED Chip Size:** SMD 335
- LED Spacing:** 0.33 in / 8.4 mm
- Length:** 16.4 ft / 5 meters long
- Width:** 0.31 in / 8 mm wide
- Height:** 0.08 in / 2 mm thick
- Cut Increment:** 1 in / 25.4 mm at cut marking
- Backing:** 3M Adhesive
- Manufacturer:** Elumalight
- Rating:** UL, ETL, RoHS
- Avg. Lifetime:** ± 30,000 - 50,000 hours
- Required:** 12V DC LED Driver

**DESCRIPTION**

12V DC LED Edge-Lit Tape Light is made with commercial-grade SMD 335 Chipsets with 120 LED Chips per meter length. Featuring 90+ CRI with high output and even illumination and perfectly designed for tradeshow decoration, exhibition lighting, retail display lighting, edge-lighting, back-lighting applications, and more. Sold in 16 ft reels.

**KEY FEATURES**

- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- SMD 335 LED Chips are bright, and energy-efficient
- No RF interference
- Up to 50,000 hours Lifespan
- UL, ETL Listed

**APPLICATIONS**

- Edge Lighting or Back Lighting Applications
- Decorative Lighting for Tradeshow, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects

