

SPECIFICATION SHEET



SPECIFICATIONS

Brightness:	Red: (540-559 Lm)
-	Green: (1300-1400 Lm)
	Blue: (400-410 Lm)
	Warm White: (1800-1900 Lm)
	Cool White: (2000-2100 Lm)
Power (Watts):	115W per sheet
Input Voltage:	24V DC
LED Chip Size:	SMD 5050
LED Chips:	288 per sheet
Dimmable:	Yes, with a dimmer
IP Rating:	IP20
Environment:	Indoor Use - Dry Location
Beam Angle:	120°
Length:	18.89 in / 480 mm long
Width:	9.45 in / 240 mm wide
Thickness:	2 mm
Required:	RGBW Controller & 24V DC LED Drivers
	(Sold Separately)
Avg. Lifetime:	± 30,000 - 50,000 hours

EL-FGP-RGBWW-24V LED RGBCW-WW Flex Grid Light Sheet

JOB NAME:

LOCATION:

QUOTE/REF#:


DESCRIPTION

The RGBCW-WW Flex Grid Light is a fully customizable and color-changing flexible LED sheet. It is perfect for backlighting displays, light boxes, letters, logos, billboards, translucent materials, and more. The high density of RGBCW-WW SMD5050 LEDs, 288 LEDs per sheet, provides vibrant, bright, and smooth illumination free of hotspots. Easily link light sheets together by using onboard connectors or soldering.

Please refer to our specified cutting recommendations. When cutting the LED sheets, it is important to cut only along the pre-marked cut lines on the sheet to maintain electrical contact.

KEY FEATURES

- Cuttable segments every 9.44 x 0.78 in
- 12 LEDs per segment
- 6 solder points per segment
- Dimmable with dimming controllers
- Dimensions: 18.89 in x 9.45 in
- Thickness: 0.08 in (2mm)
- Wire Length: 22 AWG power wires
- IP20 rated for dry environments
- 30000-50000 hours L70 lifespan
- 24V DC input
- CE-certified, RoHS



480

Unit:mm

630 Terminal Way, Costa Mesa, CA 92627 sales@step1dezigns.com | www.step1dezigns.com TF: 800.822.8527 |T: 949.270.0250 | FAX: 949.270.0253 © 2020 Step 1 Dezigns, Inc. All Rights Reserved. Specifications are subject to change without notice.