


SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



SPECIFICATIONS

- Brightness:** 800 Lumens/ft
2624 Lumens/meter
- Power (Watts):** 4.8 watt/ft
15.8 watt/meter
- Input Voltage:** 24V DC
- LED Colors:** RGBWW (Red, Green, Blue, 3000K WW)
- CRI:** ~90+
- IP Rating:** IP65
- Environment:** Wet or Dry Location
- Beam Angle:** 120°
- LED Density:** 18 LEDs/ft
300 LEDs/reel
- LED Chip Size:** SMD 5050
- LED Spacing:** 0.43 in / 11 mm
- Length:** 16.4 ft / 5 meter long
- Width:** 0.47 in / 12 mm wide
- Height:** 0.06 in / 1.5 mm thick
- Cut Increment:** 3.93 in / 100 mm at cut marking
- Backing:** 3M Adhesive
- Manufacturer:** Elumalight
- Rating:** UL, ETL, RoHS
- Avg. Lifetime:** ± 30,000 - 50,000 hours
- Required:** 24V DC LED Driver, RGBW Power Feed, RGBW Data Repeater, RGBW Controller. Sold separately.

DESCRIPTION

The LED RGBWW Tape Light is made with commercial-grade 12mm wide PCBs to ensure our color-changing RGBWW LED strips last longer and run cooler with high consistency and even illumination. It is perfect for applications that require a multi-color lighting solution, with a true 3000k Warm White light. Rated IP65 for Wet Locations.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- SMD 5050 RGBWW LEDs Chipsets are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Up to 50,000 hours Lifespan
- CE Listed, RoHS

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Backlighting or edge-lighting for sign letters
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects

