

SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



SPECIFICATIONS

Brightness	195 Lumens/ft 640 Lumens/meter
Power	2.7 watt/ft 8.9 watt/meter
Input Voltage	24V DC
LED CCT & Colors	6000K Cool White 4100K Natural White 3000K Warm White
CRI	90+
IP Rating	IP20
Environment	Indoor Use - Dry Location
LED Beam Angle	120°
LED Density	18 LEDs/ft 300 LEDs/reel
LED Chip Size	SMD 5050
LED Spacing	0.66 in / 16.7 mm
Length	12 in per segment
Width	0.31 in / 8mm wide
Height	0.06 in / 1.6 mm thick
Cut Increment	4 in / 100.16 mm at cut marking
Manufacturer	Elumalight
Rating	UL, ETL, RoHS
Avg. Lifetime	± 30,000 - 50,000 hours
Warranty	3 years limited
Power Supplies	24V DC Drivers

DESCRIPTION

The 24V DC LED High Output Flexible Tape Lights are made with commercial-grade 5050 SMD LED Chipsets to ensure our LED strips lasts longer and runs cooler with high consistency and even illumination. It is perfectly designed for trade-show decoration, exhibition lighting, retail display lighting, back-lighting applications, and more.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- SMD 5050 LED Chips are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Up to 50,000 hours Lifespan

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Backlighting or Edge-Lighting
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects

Cutable every 4 in.
at the cutmark

