

## **EL-FLRGB-W-CON**

### LED RGBW Touch Controller with Remote

**JOB NAME:** 

### SPECIFICATION SHEET



### **SPECIFICATIONS**

Input Voltage: 12V-24V DC Output Power: 6A x 4CH Output Channels: 4

Output Chaimeis. 4

Input: 2 Wire (Positive + / Negative -)

Output: 5 Wire RGBW (Positive+)
Max Load: 288 Watts (12V DC),

576 Watts (24V DC)

**Environment:** Dry Location

IP Rating: IP20

Remote Battery Type: 2 x AAA

Control Range: RF Remote Control Radius up to

100 feet (line of sight)

Previous Mode on Power Cycle: Yes

Controller Size: 3.3 in. L x 1.8 in. W x 0.8 in. H

85 mm L x 45 mm W x 20 mm H

**Remote Size:** 

4.3 in. L x 2 in. W x 0.8 in. H

110 mm L x 52 mm W x 20 mm H

Labels and Listings: CE, RoHS

Warranty: 2 Year Limited Required: Requires a nor

Requires a non-dimmable 12V DC or 24V DC

LED Driver.

# LOCATION: QUOTE/REF#:

### **DESCRIPTION**

The RGBW Touch Controller is easy to install and use. It is perfectly designed for Step 1 Dezigns RGB or RGBW LED tape and strip lights, mixing RGB and white. The RGBW Touch Controller with Remote Unit contains 12 dynamic modes, 8 dimming scales, 8 dimming speeds and comes with remote.

#### **KEY FEATURES**

- The remote controller allows for real-time color adjustment of RGB or RGB+W lights.
- The touch-sensitive color selector wheel allows you to set your lights to any desired color.
- Select custom LED colors with the color wheel remote, fade or step through colors, cycle through modes, adjust speed and brightness.
- Radiofrequency remote control works through walls with a range up to 100 feet.
- Built-In Power off memory function.

### **APPLICATIONS**

- Trade Show & Exhibit Lighting
- Retail Display Lighting
- Architectural Lighting
- Hotels, Casinos, and Clubs
- Custom Lighting Shows
- Stage Lighting

