

SPECIFICATION SHEET



JOB NAME: _____

LOCATION: _____

QUOTE/REF#: _____

CONNECTION

Electronic Dimming: 0-100%

Beam Angle: 30°

Rear Panel Controls: 4-button, DMX digital display on the rear panel

Data Link: Data linkable via 3-pin XLR cables, With Wired Digital Communication Network

Daisy Chain: 16 units (120V);
34 units (220V)

RDM Support: Supports RDM (Remote Device Management)

Mounting: Scissor Yoke & safety eye

Dimensions LxWxH: 10 in x 6.5 in x 9.25 in
256 mm x 161.7 mm x 232.5 mm

Weight: 7.5 lbs. / 3.3 kg

Ratings: ETL Approved

Lifespan: Rated at 50000 hrs



DESCRIPTION

The 7P HEX IP is a versatile, heavy-duty Par with HEX LEDs, a 30-degree beam angle, and all-metal construction. It is IP65 outdoor rated to protect against rain, snow, and dust for temporary outdoor events.

KEY FEATURES

- Light Source: 7 x 12-Watt RGBAW + UV LEDs (Red, Green, Blue, Amber, White & UV LED) - Rated at approximately 50,000 hrs.)
- IP65 Outdoor Rated
- Locking, outdoor IN/Out Power connectors
- 4 DMX Modes: 6, 7, 8 & 13-channel
- 5 Operational modes: Static Color Mode, RGBAW & UV Dimmer Mode, Program Mode, Sound Active Mode and DMX Controlled
- 63 built-in Color Macros
- Flicker Free operation (No flickering on camera)
- 5 selectable Dim Curves (Standard, Stage, TV, Architectural & Theatre)
- LED pulse and strobe effect

APPLICATIONS

- Trade Show and Exhibition Displays
- Retail Displays
- Architectural lighting for canopies, corridors, archways, windows
- Uplighting or Downlighting for wall wash applications
- Excellent for hospitality applications such as bars, restaurants, clubs, hotels
- Statue and sculpture lighting illumination
- Event and Stage Lighting

