

SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



SPECIFICATIONS

Brightness: 860 Lumens/ft
2821 Lumens/meter

Power (Watts): 8 watt/ft
26 watt/meter

Input Voltage: 12V DC

LED CCT: 3000K Warm White

CRI: 90+

IP Rating: IP20

Environment: Indoor Use - Dry Location

Beam Angle: 180°

LED Density: 100 LEDs/ft
~1600 LEDs/reel

LED Chip Size: SMD 2216

LED Spacing: 0.13 in / 3.33 mm

Length: 16.4 ft / 5 meters long

Width: 0.39 in / 10 mm wide

Height: 0.039 in / 1 mm thick

Cut Increment: 0.39 in / 10 mm at cut marking

Backing: 3M Adhesive

Manufacturer: Elumalight

Rating: UL, ETL, RoHS

Avg. Lifetime: ± 30,000 - 50,000 hours

Required: 12V DC LED Driver

DESCRIPTION

12V DC LED Ultra Density Tape Light is made with commercial-grade SMD 2216 Chipsets with 100 LED Chips per foot length. Featuring 90+ CRI with high output and even illumination and perfectly designed for tradeshow decoration, exhibition lighting, retail display lighting, back-lighting applications, and more.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- SMD 2216 LED Chips are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Up to 50,000 hours Lifespan
- UL, ETL Listed

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Backlighting or Edge-Lighting
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects

