

SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



SPECIFICATIONS

Brightness:	4200 Lumens - 24 in x 24 in 5200 Lumens - 24 in x 48 in
Power:	45 watts - 24 in x 24 in 50 watts - 24 in x 48 in
Input Voltage:	120-277V AC 60Hz
LED CCT:	4000K
CRI:	80+
Dimmable:	No
Environment:	IP20 - Dry Locations
Beam Angles:	180°
Dimensions:	24 in L x 24 in W x 2.75 in H 48 in L x 24 in W x 2.75 in H
Mounting:	Recessed
Finish:	White
Manufacturer:	Elumalight
Rating:	cETLus, CA Title 24, Energy Star, RoHS
Avg. Lifetime:	± 30,000 - 50,000 hours
Warranty:	5 Year Limited

DESCRIPTION

The Recessed, Low-profile LED Lay-In Troffers provides high-performance luminaire and general illumination.

KEY FEATURES

- Low profile design
- An energy-efficient alternative to T12 and T8 linear fluorescent troffer lights
- Excellent color consistency and superior brightness
- Non-corrosive powder-coated steel body
- Flush door frame with acrylic lens
- 120-277V AC Input
- Includes Earth Quake Clips
- Can be installed with backup batteries, sold separately
- UL, ETL Listed, DLC, RoHS Compliant

APPLICATIONS

- Commercial
- Residential
- Retail Display

ORDER SKUS

Product SKU	Size	Brightness	Wattage
EL-HPLT-2X2-40K-WH	24 in L x 24 in W x 2.75 in H	4200 Lumens	45 Watts
EL-HPLT-2X4-40K-WH	48 in L x 24 in W x 2.75 in H	5200 Lumens	50 Watts

