


SPECIFICATION SHEET

JOB NAME: _____

LOCATION: _____

QUOTE/REF#: _____



SPECIFICATIONS

- Brightness:** 450 Lumens/ft
1476 Lumens/meter
- Power (Watts):** 4.5 watt/ft
14.8 watt/meter
- Input Voltage:** 120V AC
- LED Colors:** RGBW (Red, Green, Blue, White)
- IP Rating:** IP65
- Environment:** Wet or Dry Location
- Beam Angle:** 120°
- LED Density:** 18 LEDs/ft
~300 LEDs/reel
- LED Chip Size:** SMD 5050
- LED Spacing:** 0.83 in / 21.1 mm
- Length:** 16.4 ft / 5 meter long
- Width:** 0.75 in / 19 mm wide
- Height:** 0.25 in / 6 mm thick
- Backing:** 3M Adhesive
- Manufacturer:** Elumalight
- Rating:** UL, ETL, RoHS
- Avg. Lifetime:** ± 30,000 - 50,000 hours
- Included:** 1 16 ft Reel RGBW Strip, 1 Power Feed & Controller, 5 Mounting Clips, 1 Remote

DESCRIPTION

Effective lighting is almost an indispensable aspect of an excellently designed exhibit display, tradeshow, or outdoor lighting applications. The LED RGB+W LED Strip Kit is low profile, flexible, durable, and easy to customize or install. Each 120V AC RGB+W LED Strip light may run up to 98 Ft total length with one controller device and Plug-N-Play power cord.

KEY FEATURES

- Maintenance-free, Flexible, Durable, & Easy to Install
- High shock and Vibration Resistance
- SMD 5050 LEDs Chipsets are high intensity, ultra-bright, and energy-efficient
- 90+ CRI, No RF interference
- Dimmable with compatible dimmer and power supply
- Rated IP65 for Wet Locations
- UL Listed, RoHS Compliant

APPLICATIONS

- Outdoor Decorative Lighting
- Tradeshows Exhibits, Retail Displays
- Accent and decorative lighting
- Architectural lighting for corridors, canopies, archways, or windows
- Backlighting or edge-lighting
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects

