

**SPECIFICATION SHEET**

**JOB NAME:**

**LOCATION:**

**QUOTE/REF#:**



**SPECIFICATIONS**

<b>Power:</b>	10 watts
<b>Voltage:</b>	120V AC
<b>LED CCT:</b>	3000K or 4000K
<b>Brightness:</b>	700 Lumen
<b>Beam Angle:</b>	120°
<b>CRI:</b>	90+
<b>Length:</b>	13 in / 330.2 mm
<b>Width:</b>	4.75 in / 120.65 mm
<b>Height:</b>	6.5 in / 165.1 mm
<b>Cutout:</b>	4.25 in / 107.95 mm
<b>Included:</b>	LED Light Module, Pre-installed 7.5 ft. male and 7.5 ft. female plug extension cord
<b>Mounting:</b>	Recessed. Four high tension tempered steel springs secure remodel housing to 5/8" thick (max) ceiling.
<b>Manufacturer:</b>	Elumalight
<b>Rating:</b>	Energy Star Listed, cULus Listed for Damp Location, WSEC ASTM E283 for Air-Tight, Energy Star Rated, RoHS Compliant, CA Title 24 Compliant

**DESCRIPTION**

The 4" LED Recessed Daisy Chain Light Kit is high quality, lightweight, and ideal for trade show applications. Airtight construction reduces energy costs by reducing the amount of air escaping through the ceiling. Rated for direct contact with insulation and combustible materials, Step 1 Dezigns Remodel IC housings install into existing drywall or wood ceilings with no above access. The 4" Recessed Light can be conveniently daisy-chained to additional fixtures.

**KEY FEATURES**

- "IC" Insulated ceiling housings are direct contact rated; no minimum clearance is required
- Four high tension tempered steel springs secure remodel housing to 5/8" thick (max) ceiling
- Pre-installed 7.5 ft. male and 7.5 ft. female plug extension cords are included
- Energy Star Listed
- cULus Listed for Damp Location
- WSEC ASTM E283 for Air-Tight
- Energy Star Rated
- RoHS Compliant
- CA Title 24 Compliant

**APPLICATIONS**

- LED Bathroom Lighting
- Residential Ceiling Down Lighting
- Commercial Ceiling Down Lighting
- Living Room Lighting
- Office Lighting
- LED Kitchen Lighting
- Pot Lights

