

SPECIFICATION SHEET

JOB NAME: _____

LOCATION: _____

QUOTE/REF#: _____



SPECIFICATIONS

Power:	10 watts
Voltage:	120V AC
LED CCT:	3000K or 4000K
Brightness:	700 Lumen
Beam Angle:	120°
CRI:	90+
Length:	13 in / 330.2 mm
Width:	4.75 in / 120.65 mm
Height:	6.5 in / 165.1 mm
Manufacturer:	Elumalight
Rating:	Energy Star Listed, cULus Listed for Damp Location, WSEC ASTM E283 for Air-Tight, Energy Star Rated, RoHS Compliant, CA Title 24 Compliant

DESCRIPTION

The 4" LED Recessed IC Can Light Kit is made with high-quality material, lightweight, and it is ideal for trade show applications. Airtight construction reduces energy costs by reducing the amount of air escaping through the ceiling. Rated for direct contact with insulation and combustible materials, Step 1 Designs Remodel IC housings install into existing drywall or wood ceilings with no above access.

KEY FEATURES

- "IC" Insulated ceiling housings are direct contact rated; no minimum clearance is required
- Four high tension tempered steel springs secure remodel housing to 5/8" thick (max) ceiling
- Plug N Play (Cord & Plug included)
- Energy Star Listed
- cULus Listed for Damp Location
- WSEC ASTM E283 for Air-Tight
- Energy Star Rated
- RoHS Compliant
- CA Title 24 Compliant

APPLICATIONS

- LED Bathroom Lighting
- Residential Ceiling Down Lighting
- Commercial Ceiling Down Lighting
- Living Room Lighting
- Office Lighting
- LED Kitchen Lighting
- Pot Lights

