

# EL-LWP-CCT LED CCT Horizontal Wall Pack Lights

## SPECIFICATION SHEET

JOB NAME: \_\_\_\_\_

LOCATION: \_\_\_\_\_

QUOTE/REF#: \_\_\_\_\_



60 watts



80, 120 watts

### SPECIFICATIONS

<b>Power:</b>	60, 80, or 120 watts
<b>Input Freq.:</b>	50/60 Hz
<b>Input Voltage:</b>	120-277V AC
<b>CCT Adjustable:</b>	3000K/4000K/5000K
<b>CRI:</b>	80+
<b>Min. Start Temp:</b>	-40°C / -40°F
<b>Max Oper. Temp:</b>	45°C / 113°F
<b>Dimmable:</b>	No
<b>IP Rating:</b>	IP67
<b>Environment:</b>	Wet or Dry Locations
<b>Dimensions:</b>	10.75 in L x 8.27 in W x 7.6 in H (60 watts) 14.37 in L x 9.33 in W x 7.36 in H (80 watts) 14.37 in L x 9.33 in W x 7.36 in H (120 watts)
<b>Mounting:</b>	Wall Surface Mount
<b>Manufacturer:</b>	Elumalight
<b>Rating:</b>	UL, ETL, DLC, RoHS
<b>Avg. Lifetime:</b>	± 50,000 hours
<b>Warranty:</b>	5 years limited

### DESCRIPTION

The LED CCT Horizontal Wall Pack Light fixtures are engineered to provide brilliant lighting and are efficient and energy-saving replacements for metal halide and high-pressure sodium fixtures. With the adjustable glare lens shield attached, this fixture is virtually maintenance-free.

The energy-efficient LED fixture will provide years of bright, widespread lighting with an average lifespan of estimated 50,000 hours.

Boost your energy savings with these outdoor floodlights! Applications include perimeter lighting, landscape lighting, public area floodlights, and security lighting, and lighting for building entryways.

Available in 60, 80, or 120 watts options with selectable 3000K/4000K/5000K LED CCT.

### KEY FEATURES

- Adjustable CCT 3000K, 4000K, and 5000K
- Photocell Included with Quick Disconnect
- 120V/277V Dual Voltages
- Aluminum rustproof body
- UL Certified for wet locations
- Bronze, Powder coat finish
- Polycarbonate Lens with UV Stabilization
- Long lifespan of 50,000 hours

### APPLICATIONS

- Outdoor Warehouse Lighting
- Outdoor Security Lighting
- Parking Structure Lighting
- Architectural Lighting
- Manufacturing Facilities Lighting

### ORDER SKUS

Product SKU	Wattage	Brightness	LED CCT	Beam Angle
EL-LWP-60W-CCT	60 Watt	7200 Lumens	3000K/4000K/5000K	104.4°
EL-LWP-80W-CCT	80 Watt	9600 Lumens	3000K/4000K/5000K	102.5°
EL-LWP-120W-CCT	120 Watt	14400 Lumens	3000K/4000K/5000K	104.8°

