

SPECIFICATION SHEET

JOB NAME: _____

LOCATION: _____

QUOTE/REF#: _____



SPECIFICATIONS

- Brightness:** 352 Lumens/ft
1155 Lumens/meter
- Power (Watts):** 3.2 watt/ft
10.5 watt/meter
- Input Voltage:** 24V DC
- LED CCT:** 6000K Cool White
3000K Warm White
2700K Extra Warm White
- CRI:** 90+
- IP Rating:** IP20
- Environment:** Indoor Use - Dry Location
- Beam Angle:** 120°
- LED Density:** 36 LEDs/ft
~600 LEDs/reel
- LED Chip Size:** SMD 3528
- LED Spacing:** 0.33 in / 8.4 mm
- Length:** 16.4 ft / 5 meters long
- Width:** 0.19 in / 5 mm wide
- Height:** 0.06 in / 1.6 mm thick
- Cut Increment:** 2 in / 50.8 mm at cut marking
- Backing:** 3M Adhesive
- Manufacturer:** Elumalight
- Rating:** UL, ETL, RoHS
- Avg. Lifetime:** ± 30,000 - 50,000 hours
- Required:** 24V DC LED Driver

DESCRIPTION

The 24V DC LED 5mm Width Mini High Output Tape Lights are made with commercial-grade SMD 3528 Chipsets with 36 LED Chips per foot length. The Mini LED strips featuring 85+ CRI with high output and even illumination and perfectly designed for tradeshow decoration, exhibition lighting, retail display lighting, back-lighting applications, and more. It gives you the freedom to easily design and install lighting for almost any surface or object.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- SMD 3528 LED Chips are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Up to 50,000 hours Lifespan
- UL, ETL Listed

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Backlighting or Edge-Lighting
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects

