

# EL-MLE-xxW-12V

# Dimmable LED Constant Voltage Electronic Universal Drivers 12V DC

# SPECIFICATION SHEET



#### SPECIFICATIONS

100-277V AC 50/60 Hz Input:

**12V DC Output:** Dimmable: Yes 90% Efficiency:

Power Method: Hardwiring

Input leads are 18AWG 600V, Wiring:

Output leads are 16AWG 30ÓV

Leads Max Temp: 105°C **Knockouts:** 

**Environment:** IP24 Dry or Damp Location UL Listed, CUL Listed, RoHS, CE Rating:

Manufacturer: Elumalight Warranty: 1 Year Limited

## **DESCRIPTION**

Step 1 Dezigns selection of LED Dimmable Constant Voltage Electronic Universal Drivers have the highest accuracy rating in the industry, delivering accurate dimming power. The 12V DC Drivers are generally used when you need stable voltage to your LED lights.

**JOB NAME:** 

LOCATION: QUOTE/REF#:

LED Universal Dimming Electronic Drivers are Constant Voltage, Triac (Phase) Dimmable Electronic LED Driver for Forward, and Reverse Phase Dimmers. 5% minimum load. Overload, Short circuit protection. Excellent Line and Load regulation.

It works with a wide variety of compatible dimmers, flicker-free dimming. Any kind of low voltage LED fixtures. Dimmable with a wide variety of compatible dimmers. Its low profile feature allows designers to easily incorporate it into lighting fixtures.

#### **KEY FEATURES**

- Forward and reverse phase dimming
- Easy installation
- Maintenance-free
- Solid-state construction
- High vibration and shock resistance
- Overload, short circuit, and overheat protection
- No RF interference

### **APPLICATIONS**

For use with compatible Dimmers and Constant Voltage 12V DC LED lights.

Order SKUs	Input	Output	Wattage	Class II	Dimensions (LxWxH)
			<del>                                     </del>	-	` '
EL-MLE-30W-12V	120-277V AC	12V DC	30 watts	Yes	6.79 in x 4.47 in x 1.38 in
EL-MLE-60W-12V	120-277V AC	12V DC	60 watts	Yes	6.79 in x 4.47 in x 1.38 in
EL-MLE-100W-12V	120-277V AC	12V DC	100 watts	No	7.73 in x 5.16 in x 1.54 in
EL-MLE-150W-12V	120-277V AC	12V DC	150 watts	No	9.99 in x 5.2 in x 1.82 in
EL-MLE-200W-12V	120-277V AC	12V DC	200 watts	No	9.99 in x 5.2 in x 1.82 in
EL-MLE-300W-12V	120-277V AC	12V DC	300 watts	No	9.99 in x 5.2 in x 1.82 in















