

EL-MOD3-3-110V LED Static Color 3 Watt Sign Modules

SPECIFICATION SHEET



SPECIFICATIONS

Brightness:390 Lumens/modulePower:3 watt/moduleInput Voltage:110V ACLED CCT Colors:3000K Warm White 6000K Cool WhiteCRI:90+IP Rating:IP65Environment:Outdoor Use - Wet LocationBeam Angle:160°Module Length:4.06 in / 103 mm longModule Width:0.87 in / 22 mm wideModule Height:0.35 in /9 mm thickWire Length:5 in / 127 mm (between modules)Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before installation or servicing.		
Input Voltage:110V ACLED CCT Colors:3000K Warm White6000K Cool WhiteCRI:90+IP Rating:IP65Environment:Outdoor Use - Wet LocationBeam Angle:160°Module Length:4.06 in / 103 mm longModule Width:0.87 in / 22 mm wideModule Height:0.35 in /9 mm thickWire Length:5 in / 127 mm (between modules)Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	Brightness:	390 Lumens/module
LED CCT Colors:3000K Warm White 6000K Cool WhiteCRI:90+IP Rating:IP65Environment:Outdoor Use - Wet LocationBeam Angle:160°Module Length:4.06 in / 103 mm longModule Width:0.87 in / 22 mm wideModule Height:0.35 in /9 mm thickWire Length:5 in / 127 mm (between modules)Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	Power:	3 watt/module
6000K Cool WhiteCRI:90+IP Rating:IP65Environment:Outdoor Use - Wet LocationBeam Angle:160°Module Length:4.06 in / 103 mm longModule Width:0.87 in / 22 mm wideModule Height:0.35 in /9 mm thickWire Length:5 in / 127 mm (between modules)Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	Input Voltage:	110V AC
CRI:90+IP Rating:IP65Environment:Outdoor Use - Wet LocationBeam Angle:160°Module Length:4.06 in / 103 mm longModule Width:0.87 in / 22 mm wideModule Height:0.35 in /9 mm thickWire Length:5 in / 127 mm (between modules)Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	LED CCT Colors:	3000K Warm White
IP Rating:IP65Environment:Outdoor Use - Wet LocationBeam Angle:160°Module Length:4.06 in / 103 mm longModule Width:0.87 in / 22 mm wideModule Height:0.35 in /9 mm thickWire Length:5 in / 127 mm (between modules)Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before		6000K Cool White
Environment:Outdoor Use - Wet LocationBeam Angle:160°Module Length:4.06 in / 103 mm longModule Width:0.87 in / 22 mm wideModule Height:0.35 in /9 mm thickWire Length:5 in / 127 mm (between modules)Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	CRI:	90+
Beam Angle:160°Module Length:4.06 in / 103 mm longModule Width:0.87 in / 22 mm wideModule Height:0.35 in /9 mm thickWire Length:5 in / 127 mm (between modules)Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	IP Rating:	IP65
Module Length: 4.06 in / 103 mm longModule Width: 0.87 in / 22 mm wideModule Height: 0.35 in /9 mm thickWire Length: 5 in / 127 mm (between modules)Backing: 3M AdhesiveManufacturer: ElumalightRating: UL, ETLAvg. Lifetime: ± 30,000 - 50,000 hoursWarranty: 3 years limited* WARNING:	Environment:	Outdoor Use - Wet Location
Module Width:0.87 in / 22 mm wideModule Height:0.35 in /9 mm thickWire Length:5 in / 127 mm (between modules)Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	Beam Angle:	160°
Module Height:0.35 in /9 mm thickWire Length:5 in / 127 mm (between modules)Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	Module Length:	4.06 in / 103 mm long
Wire Length:5 in / 127 mm (between modules)Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	Module Width:	0.87 in / 22 mm wide
Backing:3M AdhesiveManufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	Module Height:	0.35 in /9 mm thick
Manufacturer:ElumalightRating:UL, ETLAvg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	Wire Length:	5 in / 127 mm (between modules)
Rating: UL, ETL Avg. Lifetime: ± 30,000 - 50,000 hours Warranty: 3 years limited * WARNING: 110V AC contact may cause electrical shock and injury. Disconnect all power before	Backing:	3M Adhesive
Avg. Lifetime:± 30,000 - 50,000 hoursWarranty:3 years limited* WARNING:110V AC contact may cause electrical shock and injury. Disconnect all power before	Manufacturer:	Elumalight
 Warranty: 3 years limited * WARNING: 110V AC contact may cause electrical shock and injury. Disconnect all power before 	Rating:	UL, ETL
* WARNING: 110V AC contact may cause electrical shock and injury. Disconnect all power before	Avg. Lifetime:	± 30,000 - 50,000 hours
* WARNING: 110V AC contact may cause electrical shock and injury. Disconnect all power before installation or servicing.	Warranty:	3 years limited
	* WARNING:	110V AC contact may cause electrical shock and injury. Disconnect all power before installation or servicing.

JOB NAME:

LOCATION:

QUOTE/REF#:

DESCRIPTION

LED Static Color Sign Module lights are rated IP65 for outdoor or indoor lighting applications. They come with flexible wires and easy to install. Because the wires are flexible, you can easily arrange your LED modules around your installation as desired. It contains 3 LED Chipsets per module for a 160° beam angle. Each module is made with an injection-molded PVC plastic housing that is rigid and lightweight.

About 5 inches of wire between the LED modules. 2 modules per 1 ft. length. Each reel comes with 100 modules per string.

Each LED sign module comes with double-sided 3M foam tape on its back. Simply peel and stick the LED module to the position desired.

The LED Modules are dimmable if used with a compatible dimmer. LED dimmers are sold separately. Cut LED modules are not returnable.

KEY FEATURES

- No LED Drivers needed (110V AC input)
- Rated IP67 for Indoor or Outdoor Environments
- Easy to Install with 3M tape backing
- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- LED Chips are high intensity, ultra-bright
- Low power consumption
- No UV emissions, safe on artworks or graphics

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Retail Stores, Restaurants, Casinos, Lounges, and Residential Homes
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Backlighting or Edge-Lighting
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects



© 2020 Step 1 Dezigns, Inc. All Rights Reserved. Specifications are subject to change without notice.