

SPECIFICATION SHEET

JOB NAME: _____

LOCATION: _____

QUOTE/REF#: _____



EL-NDHD-20W-12V



EL-NDHD-40W-12V



EL-NDHD-60W-12V



EL-NDHD-100W-12V



EL-NDHD-150W-12V

SPECIFICATIONS

Input: 100-240V AC
Output: 12V DC
Power: 20, 40, 60, 100, or 150 watts options
Dimmable: No
Power Method: Hardwiring
Rating: UL Listed, CUL Listed, RoHS, CE
Manufacturer: Elumalight
Warranty: 1 Year Limited

DESCRIPTION

12V DC LED Hardwire Constant Voltage Drivers are generally used when you need stable voltage to your LED lights. It has built-in overload, short circuit, and overheat protection. They are energy efficient and ideal for powering our 12V DC LED lighting. Available in 20 watts, 40 watts, 60 watts, 100 watts, or 150 watts options.

Need help with your LED lighting applications? Our lighting experts are here to help! Contact us today for assistance with lighting plan or installation instructions.

KEY FEATURES

- Easy installation
- Maintenance-free
- Solid-state construction
- High vibration and shock resistance
- Overload, short circuit, and overheat protection
- No RF interference
- Hardwiring power method
- UL Listed power supply
- Long lifespan

APPLICATIONS

- For use with compatible Constant Voltage 12V DC LED lighting. Not for use with dimmers.

Order SKUs	Voltage	Wattage	Dimensions	IP Rating
EL-NDHD-20W-12V	12V DC	20 watts	3.75 in. L x 2 in. W x 1.5 in. H	IP20 Dry Location
EL-NDHD-40W-12V	12V DC	40 watts	4 in. L x 2.5 in. W x 1.5 in. H	IP20 Dry Location
EL-NDHD-60W-12V	12V DC	60 watts	6.4 in. L x 1.67 in. W x 1.26 in. H	IP67 Wet or Dry Location
EL-NDHD-100W-12V	12V DC	100 watts	8.25 in. L x 2.6 in. W x 1.6 in. H	IP20 Dry Location
EL-NDHD-150W-12V	12V DC	150 watts	8.98 in. L x 2.68 in. W x 1.53 in. H	IP65 Wet or Dry Location

