

SPECIFICATION SHEET

JOB NAME:

LOCATION:


QUOTE/REF#:



SPECIFICATIONS

- Brightness:** 500 Lumens/ft
- Power:** 3.6 watt/ft
- Input Voltage:** 12V DC
- LED CCT:** 6000K Cool White or 3000K Warm White
- CRI:** 90+
- IP Rating:** IP20
- Environment:** Indoor Use - Dry Location
- Beam Angle:** 120°
- Length:** 6, 12, 18, 24, 36, 43, 55, or 67 in. options
- Width:** 0.62 in / 15.7 mm wide
- Height:** 0.50 in / 12.7 mm thick
- Mounting:** Each LED Titan Light Bar includes 2 pcs metal mounting clips
- Manufacturer:** Elumalight
- Rating:** UL, ETL, RoHS
- Avg. Lifetime:** ± 30,000 - 50,000 hours
- Warranty:** 3 years limited

Length	Watts	Lumens
12"	3.6	500
18"	5.4	750
24"	7.2	1000
36"	10.8	1500
43"	12.9	1792
55"	16.5	2292
67"	20	2792



DESCRIPTION

LED High Output Titan Light Bars are ideal for displays, exhibitions, under-cabinet, cove lighting applications. It gives you the freedom to easily design and install lighting for almost any surface or objects with even lighting illumination and no hot spots.

This LED High Output Titan Light Bar is energy efficient with uniform illumination output. The sleek design allows this unit to be concealed in spaces, it can also rotate with supplied mounting clips to easily achieve desired light beam direction.

You can utilize our LED Titan Light Bar power feeds and accessories for easy plug-n-play install. Available to order in 3000k or 6000k color temperatures. Sold in various length options.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- High shock and Vibration Resistance
- LED Chipsets are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Up to 50,000 hours Lifespan
- UL, ETL Listed

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways, or windows
- Downlighting or Uplighting Applications
- Backlighting or Edge-Lighting
- Under-cabinet, Under-Counter, or cove lighting
- Custom DIY projects



SOLD SEPARATELY



<i>Order SKUs</i>	<i>Product Name</i>
EL-N-MMC	STANDARD MOUNTING CLIP
EL-N-MAGC	MAGNETIC MOUNTING CLIP

EL-N-LENS-xx	ACRYLIC WHITE FROST LENS
* Available in 12", 18", 24", 36", 43", 55", or 67" Lengths (Ordering SKU Example: EL-N-LENS-12)	



EL-N-DPF-8	8" M/F DIRECT POWER FEED
EL-N-DPF-16	16" M/F DIRECT POWER FEED
EL-N-DPF-36	36" M/F DIRECT POWER FEED



EL-N-HWPF-72	72" HARD WIRE POWER FEED
EL-N-AWPF-36	36" ANGLE H.W. POWER FEED



EL-N-JMP-8	8" M/M JUMPER CORD
EL-N-JMP-12	12" M/M JUMPER CORD
EL-N-JMP-36	36" M/M JUMPER CORD



EL-N-YC-2	2-WAY M/F POWER FEED
EL-N-YC-3	3-WAY M/F POWER FEED
EL-N-YC-5	5-WAY M/F POWER FEED



EL-N-DJ	DIRECT JOINER
EL-N-AJ	90° ANGLE JOINER



EL-N-ILSW	IN-LINE ON/OFF SWITCH
------------------	-----------------------

