

SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



DESCRIPTION

The RGB Controller with Remote contains 9 pre-programmed color-moving sequences, including speed adjustment and pause features. Need help with your RGB LED lighting applications? Our lighting experts are here to help! Contact us today for assistance with lighting plan or installation instructions.

SPECIFICATIONS

Input Voltage: 5-24V DC
Output Power: 6A x 3CH
Output Channels: 3
Input: 2 Wire (Positive + / Negative -)
Output1: 4 Wire RGB (Positive+)
Output2: 4 Wire RGB (Positive+)
Max Load: 90 Watts (5V DC),
 432 Watts (24V DC),
Standby Power: 0.5 Watt
Environment: Dry Location
IP Rating: IP20
Required: 12V DC or 24V DC LED Power Supply
Controller Size: 5 in. L x 2 in. W x 0.75 in. H
 127 mm L x 51 mm W x 19 mm H
Labels: CE, RoHS
Warranty: 2 Year Limited

KEY FEATURES

- Use the wireless remote within 100 feet, or control manually by the keys on the controller panel
- Three channel RGB control. Max 6A each channel
- Up to 31 changing modes to select, 256 grey level changing
- Each mode can select changing speed and overall brightness separately
- Level brightness and speed adjustment
- Change and Pause function
- Mode, suspend protection and memory function
- Soft switch function

APPLICATIONS

- Trade Show & Exhibit Lighting
- Retail Display Lighting
- Architectural Lighting
- Hotels, Casinos, and Clubs
- Custom Lighting Shows
- Stage Lighting