

EL-RGBFL-20 RGB LED Floodlight

SPECIFICATION SHEET



CONNECTION

Brightness: Red - 210 Lm,

Green - 450 Lm, Blue - 106 Lm

Power: 20 watts Input Voltage: 120V AC

LED Color: RGB (Red, Green, Blue)

140° **Beam Angle: IP Rating: IP65**

Environment: Wet or Dry Locations

Dimensions: 7.17 in. L x 7.05 in. W x 1.69 in. H

Mounting: Surface Mount Manufacturer: Elumalight Rating: **ETL Listed** ± 50,000 hours Avg. Lifetime: Warranty: 1 Year Limited

JOB NAME: LOCATION: QUOTE/REF#:

DESCRIPTION

RGB LED Floodlight is the perfect solution for dynamic illumination of facade structures and landscapes. With an IP66 rating, it is perfect for indoor and outdoor applications.

The RGB LED Floodlight is low maintenance and an energy-saving replacement option for traditional illumination sources. Our 20 Watt RGB Floodlight can operate as an RGB unit with a remote controller included.

KEY FEATURES

- Energy Efficient LED RGB Chipset
- Easy Installation with Mounting Bracket
- **Aluminum Rust Proof Body**
- Instant Start Electric Unit
- Suitable for Wet Location

APPLICATIONS

- **Commercial Lighting**
- **Residential Lighting**
- **Outdoor Lighting**
- Wall Wash Lighting













