

SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



SPECIFICATIONS

- Power (Watts):** 10.5 watt (EL-RPL4-CCT)
13.5 watt (EL-RPL6-CCT)
- Input Voltage:** 120V AC
- Brightness:** 600 Lumen (EL-RPL4-CCT)
800 Lumen (EL-RPL6-CCT)
- LED CCT:** 2700K / 3000K / 3500K/
- Dimmable:** Yes, Triac/ELV
- IP Rating:** IP65
- Environment:** Wet or Dry Location
- Beam Angle:** 112°
- Diameter:** 4 in / 101.6 mm
6 in / 152.4 mm
- Height:** 1.25 in / 31.75 mm thick
- Manufacturer:** Elumalight
- Rating:** UL, ETL, Title 24, ENERGY STAR
- Avg. Lifetime:** ± 30,000 - 50,000 hours
- Warranty:** 3 years limited

DESCRIPTION

The 4 or 6 in. LED Round Tunable White Panel Lights are designed for easy installation into new construction or remodel applications.

It is perfect for corridor, hallway, living room, meeting room, office, store, supermarket, exhibition, or other home and commercial use. Tunable white luminaires include an integral tunable CCT switch located on the junction box of each luminaire with a quick connect that allows for easy disconnect and mounting in the ceiling.

KEY FEATURES

- No housing required and includes pre-wired junction box
- Quick disconnect allows for easy installation Junction box includes tunable color temperature switch
- IC Air-Tight rated
- Triac or ELV dimming
- cETLus Listed for Wet locations
- ENERGY STAR certified
- Certified to the high efficacy requirements of California Title 24 JA8-2019
- Field Selectable CCT Switch (2700K, 3000K and 3500K)

APPLICATIONS

- Lighting for Tradeshows, Exhibition, Retail Displays
- Retail Stores, Restaurants, Clubs, Lounges,
- Residential Home Lighting
- LightBox Lighting
- Custom DIY projects

