

## SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



### FEATURES & SPECS

- 360° rotation and a 90° tilt range for added versatility
- 9W / 780 lm
- 2700K, 3000K, 3500K, 4000K, 5000K CCT Selectable
- IC Rated for direct contact to insulation
- CRI 90+
- 120V
- ETL Listed for damp locations
- CA Title 24 compliant
- Dimmable Triac/ELV

### Technical Details

**Optics:** Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

**Construction:** IC rated driver and fixture are tested and approved for direct contact with insulation. Aluminum die-cast trim with durable powdercoat finish preventing rust and paint cracking. Plenum rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two 7/8" knockouts with slots for pryout.

**Installation:** Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut out template provided for accurate hole size for proper trim installation.

**Electrical:** Included driver connects directly to 120V power supply. Standard input wattage is 9W, 85 lumens per watt. Replaces 75W incandescent.

**Dimmability:** Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the ELM System Dimmer Compatability List.

**Listings:** ETL Listed for DAMP Locations. IC-Rated for direct contact with insulation. Air Tight certified in accordance with ASTM E283-2004. California Title 24 Compliant (JA8-2016-E)

**Warranty:** 5-year limited warranty.

### OPTIONS



White  
EL-RG416W



White  
EL-RG416BZ

### DIMENSIONS

