

SPECIFICATION SHEET

JOB NAME:

LOCATION:

QUOTE/REF#:



DESCRIPTION

The LED MR-16 Mini Recessed Gimbal Ring Fixture ideal for use in shelving, cabinets and display cases. It swivels up to 35° for the desired lighting direction.

It is supplied with 5 watts 3000K Warm White or 5000K Cool White MR-16 LED bulb options and metal housing with a cutout template for various installation projects. It can be used with housing for permanent installation or plug & play system.

SPECIFICATIONS

- Brightness:** 400 Lumens
- Power (Watts):** 5 Watt
- Input Voltage:** 12V AC/DC
- LED CCT:** 3000K or 5000K
- LED Bulb:** MR-16
- Dimmable:** Yes, with Dimmable Driver
- IP Rating:** IP20
- Environment:** Indoor Use - Dry Location
- Beam Angle:** 15 - 40°
- LED Density:** 1 LEDs
- Cut-out:** 2.75 in / 69.85 mm Diameter
- Gimbal Size:** 3.5 in / 88.9 mm
- Gimbal Depth:** 3 in / 76.2 mm
- Finish:** Black, White, Chrome, Brush Nickel, Bronze
- Manufacturer:** Elumalight
- Rating:** UL, ETL Listed
- Avg. Lifetime:** ± 30,000 - 50,000 hours
- Required:** The LED MR-16 Mini Gimbal Ring Trim requires 12V AC/DC LED Power Supply. Sold separately.

KEY FEATURES

- Maintenance-free
- Solid-State Construction
- No IR or UV radiation
- Suitable for flat ceiling or under-cabinet installations
- Easy to mounting and install with tension spring clamps
- LEDs bulbs are high intensity, ultra-bright, and energy-efficient
- No RF interference
- Long lifespan: Up to 50,000 hours

APPLICATIONS

- Decorative Lighting for Tradeshows, Exhibition, Retail Displays
- Architectural lighting for corridors, canopies, archways,
- Downlighting or Uplighting Recessed Applications
- Under-cabinet, Under-Counter, or accent lighting

