

**SPECIFICATION SHEET**

JOB NAME:

LOCATION:

QUOTE/REF#:



**SPECIFICATIONS**

**Brightness:** 3200 Lumens  
**Power:** 36 watts  
**Input Line Freq:** 50/60 Hz  
**Input Voltage:** 120-277V AC  
**LED CCT:** 4000K  
**CRI:** 80+  
**Min. Start Temp:** -20°C / -4°F  
**Max Oper. Temp:** 40°C / 104°F  
**Dimmable:** 10% 0-10V Dimmable  
**IP Rating:** IP65  
**Environment:** Wet or Dry Locations  
**Beam Angles:** 120°  
**Dimensions:** 48 in L x 5.31 in W x 3.94 in H  
**Mounting:** Ceiling Surface Mount  
**Manufacturer:** Elumalight  
**Rating:** UL Listed  
**Avg. Lifetime:** ± 50,000 hours  
**Warranty:** 5 years limited

**DESCRIPTION**

Step 1 Dezigns 36-watt LED vapor tight linear fixture is built to provide high-quality illumination for parking structures, automotive garages, utility lighting, and stairwell lighting.

UL listed and IP65 rated for wet locations, indoors or outdoors, this fixture features a 48-inch, one-piece, vapor tight, non-corrosive, polycarbonate lens and body for long interior or exterior lifespan

**KEY FEATURES**

- Instant-on flat panel LED
- 10% 0-10V Dimmable
- 50,000 hours lifespan
- Polycarbonate construction
- Stainless steel clips
- Non-corrosive, Flame and vandalism resistant
- Rated for wet locations IP65
- Light grey case with clear diffuser lens

**APPLICATIONS**

- Garages, Carports, Car Wash
- Parking Structures
- Laundry Room
- Walk Ways
- Warehouses
- Freezer
- Outdoor Locations

