

EL-WRP-5X48-CCT | EL-WRP-9X48-CCT

LED CCT Selectable Wraparound Light Fixtures

SPECIFICATION SHEET



JOB NAME:

LOCATION:

QUOTE/REF#:

SPECIFICATIONS

Brightness:	4000 Lumens
Power:	40 watts
Input Voltage:	120-277V AC 60 Hz
LED CCT:	CCT Selectable 3000K, 4000K, or 5000K
Beam Angle:	120°
CRI:	80+
Dimmable:	Yes, with compatible dimmer
IP Rating:	IP20
Environment:	Dry Locations
Dimensions:	48.74 in L x 5 in W x 2.25 in H 48.03 in L x 8.66 in W x 2.63 in H
Mounting:	Surface mounting for ceiling or wall mounting, compatible with most ceiling types.
Finish:	White
Manufacturer:	Elumalight
Rating:	cETLus, CA Title 24, Energy Star, RoHS
Avg. Lifetime:	± 30,000 - 50,000 hours
Warranty:	5 Year Limited

DESCRIPTION

The new LED Wraparound Light Fixture has a prismatic acrylic diffuser providing an even light distribution. Its slimline profile allows it to be undetected when mounted to the ceiling. Use for corridors, stairwells, utility closets, and small office areas.

KEY FEATURES

- Replaces Fluorescent Wraparound Light Fixture with Energy Efficient LED
- Acrylic, high-impact, injection-molded prismatic basket diffuser with a flat bottom and vertical sides.
- The finish is high-gloss baked white enamel over rust-inhibiting phosphate coating for maximum corrosion resistance
- ETL, JA8 Title 24, DLC 5.1 Listed
- Damp or Dry Locations

APPLICATIONS

- Corridors
- Stairwells
- Warehouses
- Offices
- Laundry Rooms
- Work Areas
- Garages
- Carports
- Walk Ways

ORDER SKUS

Product SKU	Size	Brightness	Wattage
EL-WRP-5X48-CCT	48.74 in L x 5 in W x 2.25 in H	4000 Lumens	40 Watts
EL-WRP-9X48-CCT	48.03 in L x 8.66 in W x 2.63 in H	4000 Lumens	40 Watts

