

WL-LED130

Step And Wall Light

Project:	
Location:	

Fixture Type:

Model & Voltage	Color Temp & CRI	Lumens	Finish
WL-LED130 120 VAC	Amber 90	40	BK Black on Aluminum
	White 90	40	BZ Bronze on Aluminum
WL-LED130F 277 VAC	Amber 90	40	SS Stainless Steel
	White 90	40	WT White on Aluminum

Example: WL-LED130-AM-BK

DESCRIPTION

WAC Lighting Step and Wall Lights are designed to seamlessly blend into any architecture featuring a sleek interchangeable magnetic faceplate with no visible hardware. These luminaires offer enhanced energy-efficient functionality and optimized light output to adequately illuminate stairs, walls and walkways with little or no glare. Light engine is IP66 sealed for both indoor and outdoor applications.

FEATURES

- Diffuse tempered glass provides even illumination
- Magnetized design for easy installation and maintenance
- Low profile, flush to wall aesthetics with no visible hardware
- · Can be mounted vertically or horizontally
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast corrosion resistant aluminum alloy, Cast 316

marine grade stainless steel

Power: 3.5W, 3W

Input: 120 VAC, 50/60Hz, 277 VAC

Dimming: ELV: 100-10%,
Light Source: Integrated LED
Rated Life: 50000 Hours

Mounting: Fits into 2" x 4" J-Box with minimum inside dimensions of

3"L x 2"W x 2.5"D

Finish: Enamel Coated:White on Aluminum, Enamel

Coated::Stainless Steel, Enamel Coated:::Bronze on Aluminum, Enamel Coated:::Black on Aluminum

-40°F to 104°F (-40°C to 40°C)


Standards: ETL, cETL, Wet Location Listed, IP66, Title 24 JA8-2019

Compliant, ADA

FINISHES:



LINE DRAWING:



REPLACEMENT PARTS

Operating Temp:

W-4071-130-BK - LED130 Cover Plate BK W-4071-130-BZ - LED130 Cover Plate BZ W-4071-130-SS - LED130 Cover Plate SS W-4071-130-WT - LED130 Cover Plate WT

