

WAC LIGHTING

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

WL-LED140

Step And Wall Light

| Model & Voltage | Color Temp & CRI | Lumens | Finish |
|--------------------|----------------------|--------|---|
| WL-LED140 120 VAC | Amber 90 White 90 | 3 3 | BK Black on Aluminum BZ Bronze on Aluminum |
| WL-LED140F 277 VAC | Amber 90 White 90 | 3 3 | WT White on Aluminum |

Example: **WL-LED140-AM-BK**

DESCRIPTION

WAC Lighting Step and Wall Lights are designed to seamlessly blend into any architecture featuring a sleek interchangeable magnetic faceplate with no visible hardware. These luminaires offer enhanced energy-efficient functionality and optimized light output to adequately illuminate stairs, walls and walkways with little or no glare. Light engine is IP66 sealed for both indoor and outdoor applications.

FEATURES

- Geometric design with downward illumination
- Magnetized design for easy installation and maintenance
- Low profile, flush to wall aesthetics with no visible hardware
- 5 year warranty

SPECIFICATIONS


| | |
|------------------------|---|
| Construction: | Die-cast corrosion resistant aluminum alloy |
| Power: | 3W, 3.5W |
| Input: | 277 VAC, 50/60Hz, 120 VAC |
| Dimming: | , ELV: 100-10% |
| Light Source: | Integrated LED |
| Rated Life: | 50000 Hours |
| Mounting: | Fits into 2" x 4" J-Box with minimum inside dimensions of 3"L x 2"W x 2.5"D |
| Finish: | Enamel Coated: White on Aluminum, Bronze on Aluminum, Black on Aluminum |
| Operating Temp: | -40°F to 104°F (-40°C to 40°C) |
| Standards: | ETL, cETL, Wet Location Listed, IP66, ADA, Title 24 JA8-2019 Compliant |

REPLACEMENT PARTS

- W-4091-140-BK - LED140 Cover Plate BK
- W-4091-140-BZ - LED140 Cover Plate BZ
- W-4091-140-WT - LED140 Cover Plate WT



FINISHES:



LINE DRAWING:

