

WATER REVIVAL SYSTEM™

Our patent-pending 10-STAGE Water Revival System™ has set a new standard within the consumable water filtration industry. The first of its kind producing water 100% free of invasive acids, 100% free of undesirable contaminants, a high-alkaline pH, and an ideal low TDS, all verified by a thorough third-party lab chemical analysis.

Next Generation High Efficiency Reverse Osmosis System sets the new standard for high alkaline pH H₂O.

Proprietary Dual Deionization stages remove remaining undesirable solids and acids (i.e., Acid Rain) left behind by traditional filter systems.

Remineralization stage increases beneficial ions in water, like Magnesium Bicarbonate, which gives the water its crisp taste, light body, and clean finish.

Lodestones & quartz crystals recharge and reprogram water naturally, just like a living stream system.

Aquatec Permeate Pump increases system efficiency and boosts water pressure at the system faucet or to other points of use like refrigerators and/or hot+cold dispensers.

WRS-UC4



AMERICAN
★ MADE ★



 PRISTINEHYDRO®

WATER REVIVAL SYSTEM™

SYSTEM SPECIFICATION

The Under-Counter 10-Stage Water Revival System™ will provide you with years of PristineHydro® water on demand – right from the comfort of your own home! A 75 gallon per day rated membrane delivers an eco-friendly 1 to 1 waste to recovery ratio.



STAGE 1	5 MICRON
STAGE 2, 3	KDF + CARBON
STAGE 4	HIGH EFFICIENCY REVERSE OSMOSIS
STAGE 5, 6	DUAL DEIONIZATION
STAGE 7	REMINERALIZATION
STAGE 8	COCONUT CARBON
STAGE 9, 10	RESTRUCTURING + RECHARGING



FEED WATER REQUIREMENTS

Feed Water	Potable, municipal water
Feed Pressure	40 to 80 PSI
Feed Temperature	45 Deg. F. to 100 Deg. F.
Total Dissolved Solids	600 PPM or less
Chlorine	<1.0 mg/l max
pH	4-8
Turbidity	<1.0 NTU (visibly clear)
SDI	<5
Iron	0.2 mg/l or less
Manganese	0.03 mg/l or less

REPLACEMENT PARTS

When properly maintained, this system will provide you with years of trouble-free operation. The cartridges in this system must only be replaced with PristineHydro® Authorized Replacement Filters and on a regular basis in order to maintain system efficiency and to ensure water production that is 100% free of all undesirable acids and contaminants. These cartridges are designed to work together as a system and should be replaced at the recommended intervals.

12 MONTH KIT	5 MICRON	KDF + CARBON
24 MONTH KIT	PRIMARY DEIONIZATION	SECONDARY DEIONIZATION
36 MONTH KIT	HIGH EFFICIENCY REVERSE OSMOSIS	REMINERALIZATION (INCLUDES COCONUT CARBON)