

Detec Full HD Fixed Cube IP Camera

DTC-FC2MPWDPIRP

1/2.7" CMOS, 2.8mm, 120dB WDR, H.265+, 1080p, 25/30fps, Two-way Audio, Built-In Mic & Speaker, Micro SD slot, 10m IR & PIR, PoE



Key Features

- 1920 x 1080@30fps
- IR: 10 m
- PIR: 10m
- H.265, H.265+
- 120dB WDR
- Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
- PoE
- EXIR

Detec AS – Sandakerveien 24C, Bldg. A4, N-0473 Oslo, NORWAY – www.detec.no

Detec AS continuously develop products, and reserve the right to change specifications and prices without prior warning. This document is under constant change, and may be subject to error.

Specification

Camera

Image Sensor:		1/2.7" Progressive Scan CMOS
Signal System:		PAL/NTSC
Min. Illumination:		Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR
Shutter time:		1/3 s to 1/100,000 s
Slow shutter:		Support
Lens:		2.8 mm: horizontal FOV: 114°, vertical FOV: 62°, diagonal FOV: 135°
Lens Mount:		M12
Adjustment Range:		Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°
Day& Night:		IR Cut Filter
Wide Dynamic Range:		120 dB
Digital noise reduction:		3D DNR
Focus:		Fixed

Compression Standard

Video Compression:		H.265+/H.265/H.264+/H.264/MJPEG
H.264 code profile:		Main Profile/High Profile
Video bit rate:		256Kbps~16Mbps
Audio Compression:		G.711/G.722.1/G.726/MP2L2/PCM
Audio bit rate:		64Kbps(G.711)/ 16Kbps(G.722.1)/ 16Kbps(G.726)/ 32-160Kbps(MP2L2)
Triple Streams:		Yes

Image

Max. Image Resolution:		1920 x 1080
Frame Rate:		50Hz: 25fps (1920 x 1080, 1280 x 960, 1280 x 720) 60Hz: 30fps (1920 x 1080, 1280 x 960, 1280 x 720)
Sub Stream:		50Hz: 25fps (640 x 480, 640 x 360, 320 x 240) 60Hz: 30fps (640 x 480, 640 x 360, 320 x 240)
Third Stream:		50Hz: 25fps (1920 x 1080, 1280 x 720, 640 x 360, 352 x 288) 60Hz: 30fps (1920 x 1080, 1280 x 720, 640 x 360, 352 x 240)
Image Enhancement:		BLC/3D DNR
Image Settings:		Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
ROI:		Support 1 fixed region for each stream
Day/Night Switch:		Day/Night/Auto/Schedule

Detec AS – Sandakerveien 24C, Bldg. A4, N-0473 Oslo, NORWAY – www.detec.no

Network

Network Storage:	microSD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR
Alarm Trigger:	Motion detection, video tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error
Protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, QoS, IPv6
General Function:	One-key reset, Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering
System Compatibility:	ONVIF (Profile S, Profile G), ISAPI

Interface

Audio:	1 built-in mic, 1 built-in speaker, mono sound
Communication Interface:	1 RJ45 10M / 100M Ethernet interface
On-board storage:	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
Reset Button:	Yes

Audio

Environment Noise Filtering:	Support
Audio Sampling Rate:	8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz

Smart Feature-set

Line Crossing Detection:	Cross a pre-defined virtual line
Intrusion Detection:	Enter and loiter in a pre-defined virtual region
Recognition:	Face Detection

General

Operating Conditions:	-10 °C – 40°C (14 °F – 104 °F) Humidity 95% or less (non-condensing)
Power Supply:	12 VDC ± 25%, PoE (802.3af Class3)
Power Consumption:	12 VDC, 0.5A, max. 6W, Φ 5.5 mm coaxial plug power PoE (802.3af, 36V to 57V), 0.2 A to 0.1 A, max. 7W
IR Range:	Up to 10m
PIR:	10m
Dimensions:	102.8 mm x 65.2 mm x 32.6 mm (4.1" x 2.6" x 1.3")
Weight:	Camera: Approx. 128 g (0.3 lb.)

Dimensions

