

## Detec 19" 2U IP Video Server, 8x HDDs

*DTC-IVS-XE6C-HD8v2*



- **IP Video Surveillance Server with Microsoft Windows 11 PRO OS**
- **Intel® Xeon® Processor E-2356G 6 Cores/12 Threads, 12MB Cache, 5.0 GHz**
- **HDMI and VGA Video Output**
- **1 x Dual Port Intel X710-AT2 Gigabit 10G LAN Controller (2 x GbE LAN)**
- **RS-232 and RS-485 (on main board)**
- **1 x USB 3.1 Interface in Front, 6 x USB 3.1 in Rear**
- **8 x Hard Disk Drive Slots (HDDs), 2x 4TB storage included**
- **19" 2U Rack-Mount Chassis (rack rails included in the box)**

## Specification

### Capacity

<b>Max. recommended number of cameras:</b>	Detec Next Core & Advanced camera licenses: 100x Full HD cameras @ 2Mb/s Detec Next Advanced+ camera licenses: 16x Full HD cameras @ 2Mb/s Detec Next PRO camera licenses: 8x Full HD cameras @ 2Mb/s
--	---

### Processor

<b>Model:</b>	Intel® Xeon® Processor E-2356G (6 Cores/12 Threads, 12MB Cache, 5.0GHz) Socket LGA1200
---------------	--

### Mainboard

<b>Model:</b>	Asus, P12R-E-10G-2T ATX, with ASMB10-iKVM
---------------	---

### Memory

<b>Memory size:</b>	16GB (2x 8GB) Maximum up to 128GB UDIMM, DDR4 3200/2933/2666 UDIMM (32GB, 16GB, 8GB)
---------------------	--

### Operating System

<b>Type:</b>	Microsoft Windows 11 Pro, 64-bit
--------------	----------------------------------

### Video & Audio Output

<b>HDMI output:</b>	Resolution: 4096 × 2304/60Hz (4K)
<b>VGA output:</b>	1 - Resolution: 1920 × 1200/60Hz
<b>Audio output:</b>	High Definition Audio, 1/4/5.1/7.1-channel, support for S/PDIF Out

### System Drive

<b>SSD:</b>	128GB M.2 PCIe x NVMe SSD
-------------	---------------------------

### Storage

<b>SATA:</b>	8x hot-swappable SATA3 6Gb/s (by 4 Mini-SAS HD connectors) interfaces for 8x HDDs
<b>Storage Capacity:</b>	8TB (2x 4TB HDDs) included Up to 176TB total storage capacity, 22TB capacity of each disk



### External Interface

<b>Audio:</b>	N/A
<b>Network interface:</b>	1 x Dual Port Intel X710-AT2 Gigabit 10G LAN Controller (2 x GbE LAN) + 1 x Mgmt LAN
<b>USB interface:</b>	Front panel: 1 × USB 3.2 Gen 1 Rear panel: 2 × USB 3.2 Gen 2, 2 × USB 3.2 Gen 1
<b>Serial interface:</b>	RS232, RS485 (on Mother board) and PS/2 interface (Rear)
<b>Alarm in/out:</b>	N/A

### General

<b>Power supply:</b>	550W, 100 ~ 240 VAC, 10-5A, 50 ~ 60 Hz
<b>Consumption (incl. 2x HDDs):</b>	Max. 146W, idling 49W
<b>Working temperature:</b>	10 °C ~ +50 °C
<b>Working humidity:</b>	10% ~ 90% (Non condensing)
<b>Chassis:</b>	19-inch 2U rack-mounted chassis with rack rails (included in the box)
<b>Dimensions (W × D × H):</b>	432 × 559 × 90mm (17" × 22" × 3.5")
<b>Dimensions bezel &amp; ears:</b>	483 × 600 × 90mm (19" × 23.6" × 3.5")
<b>Package Dimensions:</b>	83 × 64 × 22cm (32.7" × 25.2" × 8.7")
<b>Weight (incl. 2x HDDs):</b>	Gross weight: 20.1kg (44.3lbs) / Net weight: 13.5kg (29.8lbs)

<b>Available Options</b>	
Memory, 32GB (2x 16GB RAM units), as a replacement for the standard 2x 8GB RAM units	DTC-CMP-RAM32GB (or ask for more, max. 128GB)
Dual power supply, 2 x 800W, as a replacement for the standard single 500W power supply	DTC-CMP-DPSU

<b>Accessories</b>	
Devices to consider: - Monitor w 1080p resolution, HDMI (or VGA) - Network switch with cameras	
 <p>Detec Next Video Surveillance Software</p>	 <p>Storage drives 2, 4, 6, 8, 10, 12, 14, 18, 22 TB HD-xxTB Options also available with SSD's</p>

