

Line Interactive UPS

Uluru Series



600VA - 2000VA



Features:

- AVR boost and buck
- Cold start function
- USB interface for power management
- Built-in self-diagnosis function
- Modem/LAN internet protection
- User friendly LCD display
- Fastest charging capacity
- Auto charge even when UPS is turned off
- Auto restart on resumption of AC supply

Line Interactive UPS

UPS SPECIFICATIONS:

Model		Uluru 600	Uluru 800	Uluru 1200	Uluru 1500	Uluru 2000
Capacity	VA/W	600VA/360W	800VA/480W	1200VA/720W	1500VA/900W	2000VA/1200W
Input	Voltage	110/120 VAC or 220/230/240 VAC				
	Voltage Range	81~145 VAC / 162~290 VAC				
	Frequency Range	60/50 Hz (auto sensing)				
Output	AC Voltage Regulation (Battery Mode)	±10%				
	Frequency Range (Battery Mode)	60 Hz or 50 Hz ±1 Hz				
	Transfer Time	Typical 2-6 ms, 10ms maximum				
	Waveform (Battery Mode)	Simulated Sine Wave				
Battery	Battery Type & Number	12 V/7AH x 1	12 V/9AH x 1	12V/7AH x 2	12V/9AH x 2	
	Typical Recharge Time	6-8 hours recover to 90% capacity				
Indicators	AC Mode	Green LED lighting			The 5th Green LED Lighting. (The 1st to 4th green LED lighting to indicate load level) LED1 (green): >100% load level LED2 (green): >75% load level LED3 (green): >50% load level LED4 (green): >25% load level	
	Battery Mode	Amber LED flashing			The 5th Green LED light blinking. (The 1st to 4th green LED lighting to indicate battery capacity) LED1 (green): battery voltage >25V LED2 (green): battery voltage >23V LED3 (green): battery voltage >22V LED4 (green): battery voltage >21V	
	Fault	Red LED lighting				
Protection	Full Protection	Discharge, overcharge and overload protection				
Alarm	Battery Mode	Sounding every 10 seconds				
	Low Battery	Sounding every second				
	Overload	Sounding every 0.5 second				
	Battery Replacement Alarm	Sounding every 2 seconds				
	Fault	Continuously sounding				
Physical	Dimension (DxWxH) mm	298 x 101 x 142		338 x 149.3 x	380 x 158 x 198	
	Net Weight (kg)	4.25	4.9	8	11.1	11.5
Operating Environment	Humidity	0-90 % RH @ 0- 40°C (non-condensing)				
	Noise Level	Less than 40dB				
Management	Optional USB / RS-232 Port	Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC				

* Product specifications are subject to change without further notice