

xSiCute IP54 Fibre Splice & Coupler Termination Box



xSiCute IP54 rated moulded plastic external connection box is UV and weather resistant providing protection from dust and water ingress. Suitable for use as a breakout box or a splice enclosure. Supplied with 1 x 12 position built in splice tray and able to accept 16 x LC duplex or 16 x SC simplex couplers (not supplied with termination box). Suitable for external use and can be mounted on walls or poles.

The screw lockable lid is hinged and opens to 180 degrees allowing access and re-entry to the splicing and patching areas. With 2 x input ports for up to 12mm dia cable with built in cable retention and 16 x outlet ports for duplex or simplex drop cables. A write on label on the inside of the box allows identification of fibres.

- IP54 rating, UV and weather resistant.
- Suitable for external use.
- With 1 x 12 position splice trays.
- Accepts 16 x LC duplex/SC simplex couplers.
- Can be wall or pole mounted.
- Hinged screw lock lid.
- Multiple cable entry points.
- Dimensions: 260 x 320 x 90mm.

Kit Contains:

- 1 x Built in 12 position Splice holder & cable management.
- 12 x 60mm Splice Protectors.
- 12 x cable ties.
- 4 x wall mount screws and rawl plugs.
- 4 x adjustable rubber cable entry seals.
- 1 x roll of tape.
- 2 x 500mm length tube buffers.

Product Part Numbers:

Description	Part Number
External IP54 Termination Box with 1 x 12 position splice tray*	FESC-9223

*Also accepts up to 16 x LC duplex or 16 x SC simplex couplers. The couplers are not supplied with the termination box, see separate product spec.