

xSiCute IP65 Fibre Splice & Coupler Termination Box



xSiCute IP65 rated moulded plastic external connection box for up to 108 fibres. Suitable for use as a breakout box or a splice enclosure. The patching area accepts up to 54 x LC duplex couplers or 54 x SC simplex couplers. Supplied with 3 x 24 position fibre splice trays and can accept an additional three trays if required. Trays are hinged to allow access to other trays and open beyond 90 degrees enabling unencumbered access to installed fibres. May be externally mounted on poles or walls.

With 15 x input/output ports with a cable loop facility for branch cable applications. When being used as a breakout box 12 of the ports will hold up to 4 x simplex or duplex drop cables.

A hinged lid opens to 180 degrees for easy access to the splicing and patching areas. A lid locking mechanism prevents unauthorised access & can also be screwed in place. UV resistant weather-proof providing protection from dust and water ingress.

- IP65 rating.
- Accepts up to 108 fibres.
- Breakout box/splice enclosure.
- Accepts fibre couplers and/or splice trays.
- Hinged lid & splice trays allow easy access.
- Can be wall or pole mounted.
- Multiple cable entry points.
- Dimensions: 398 x 327 x 118mm.

Kit Contains:

- 3 x 24 way splice holders.
- 72 x 40mm splice protectors.
- 1 x 900mm length buffer tubing.
- 16 x cable ties.
- 1 x Roll of tape.
- 4 x wall mount screws & rawl plugs.

Product Part Numbers:

Description	Part Number
External IP65 Fibre Splice & Coupler Termination Box*	FESC-9556
Additional 24 Position Fibre Splice Tray	FESC-9561

*With 3 x 24 way splice trays as standard, will accept a further 3 x trays.