ROBOARD

Model: VRD-N0612-SD-R

MIOUGI. VDD-1100 12-3D-D		
Material:	Silicone	
Colour:	Black	
Beam Angel:	120°	
Channel Length:	5m (16.4ft) Max	
Channel Width:	6mm (0.23")	
Channel Height:	12mm (0.47")	


Job Name:	
Distributor:	

Type: _

VBD-N0612-SD-B (5 meters) **SKU:** 666561432935




Model: VBD-N0612-SD-B



VBD-N0612-SD-B is designed to meet your needs with exceptional performance and quality. Please note that while this product is built to excel in various conditions, it is not recommended for extended exposure to strong UV rays or direct sunlight. If you intend to utilize the VBD-N0612-SD-B outdoors, we strongly recommend providing ample shade or protective cover to shield it from direct sunlight.

ACCESSORIES (Sold Separately)

End Caps (1 Pair/bag)	Mounting Clips (10 PCs/bag)	Flexible Clips (1 Meter)	Linear Mounting (1 Meter)
		Height 12 min	
Model: VBD-EN0612-B SKU: 666561432942	Model: VBD-CLN0612-MC SKU: 666561432973	Model: VBD-CLN0612-FC SKU: 666561432959	Model: VBD-CLN0612-LI SKU: 666561432966



LED Type: VBDFS-E2835-XXXX-168-24-NS-8 2700K • 3000K • 3500K • 4000K • 5000K **Colour:**

	Wattage	Brightness
Per Foot	3.5W/ft	450Lm/ft
Per Meter	12W/m	1475Lm/m





DESCRIPTION

Flexible 8mm-wide linear LED strip, specially designed for our Flexible Neon Channels, does not include double-sided 3m tape so that it can be easily inserted into the neon channel. can be cut every 7 LEDs (42mm or 1.63 inches). These LED strip lights are crafted from premium materials and engineered for professional lighting applications. Each strip light starts with a robust dual-core copper printed circuit board (PCB), which is then fitted with an array of chips and color options through soldering.

DIMENSIONS



Job Name: _ **Distributor:** Type:







666561433147

666561433154 666561433161





666561433178 666561433185

SPECIFICATIONS

Model:	VBDFS-E2835-xxxx-168-24-NS-8		
Color Temperature:	2700K • 3000K • 3500K • 4000K • 5000K		
LED Type:	2835 SMD		
LED Qty:	168 LEDs per meter		
Input Voltage (VF):	24V DC		
Power:	12W per meter (3.5W/ft)		
Brightness:	1475 Lm/meter (450 Lm/ft)		
Lifespan:	>50,000 hours		
PCB:	4oz PCB, Double-side, white colour 8mm width		
Rendering Index (Ra):	CRI>95		
Beam Angle:	120°		
Dimmable:	Yes		
Cut Size:	Every 7 LED chips (1.63")		
Operating Temperature:	-15°C to +40°C		
Dimensions:	8mm (0.3")		
Certificates:	UL / RoHs		



Back Side



COMPATIBLE SILICONE NEON CHANNELS (Sold Separately)



Model: VBD-N0612-SD-B **SKU:** 666561432935



Model: VBD-N0612-SD-W **SKU:** 666561432980



Model: VBD-N1212-SF-B **SKU:** 666561432683



Model: VBD-N1212-SF-W **SKU:** 666561432737



Model: VBD-N2020-SFD-W **SKU:** 666561432881

For more information about our products and services, please visit our website: www.veroboard.com