



SPECIFICATIONS

DRIVETRAIN	
CRANKSET	Prowheel Zephyr, 22/36, External BB, Black
CASSETTE	Shimano HG-50-10 10 Speed 11-36t
REAR DER	Shimano XT M786 Shadow Plus Long Cage, Silver
FRONT DER	Shimano Deore M618-D, Down Swing, Dual Pull
SHIFTERS	Shimano Deore 10 Speed, Black
SUSPENSION	
FORK	SBC Alloy, 26" Rigid, 150x15mm Thru Axle
WHEELS	
HUBS	SUNRingle SRD TA, 15x150mm F / 12x197mm R
RIMS	SUNRingle Mulefut 80SL, Tubeless Ready
TYRES	VEE Tire Bulldozer 26x4.7", Foldable, Tubeless Ready, 120TPI
COCKPIT	
SEATPOST	Surface Aluminium, Black
SADDLE	Surface Ergo, Cromo Rails
HANDLEBAR	Surface Alloy Handlebar, Dia:31.8mm, Backsweep:9°, Rise 5mm;
STEM	Surface Alloy Stem, 31.8mm, Rise 6°, with stainless steel bolts;
FRAME	
FRAME	26" Butted 6061 Aluminium, Tapered 1-1/8"-1.5" headtube, 197mm x 12mm Thru Axle Dropouts, 100mm BB width
BRAKES	
BRAKE SET	Shimano M315 Hydraulic Disc Brakes, Resin Pads, Rotors: Shimano SM-RT26 180mm/160mm, 6 Bolt
WEIGHT	
WEIGHT	TBA
WEIGHT LIMIT	120kg

OVERVIEW

Ride all year long with the Scoop Fatty! Sand, snow or mud, these large 'Bulldozer' tyres 'truck' over everything. Whether it is a relaxed ride on the beach or bombing down trails, the 4.7" tyres offers excellent grip when climbing or cornering. The updated geometry, plenty of gear options on the 2x10 setup, an alloy rigid fork and Shimano Hydraulic disc brakes makes for the perfect weekend warrior Fatbike.

FEATURES

- 6061 Alloy Fatbike specific 26" frame, tapered headset, Thru Axle
- SBC Alloy Fork, 26" Rigid, 150x15mm Thru Axle
- SUNRingle MuleFut 80SL tubeless wheelset
- WEIGHT: TBA

GEOMETRY

TYPE	S	M	L	XL
SEAT TUBE C/T	380	430	480	530
HEAD TUBE ANGLE	69.5	69.5	69.5	69.5
SEAT TUBE ANGLE	73	73	73	73
TOP TUBE	570	600	622	645
REACH	388	418	438.6	457.3
CHAINSTAY LENGTH	450	450	450	450
BB HEIGHT	318	318	318	318
WHEELBASE	1090	1120	1142	1166
HEAD TUBE LENGTH	110	110	115	130
STACK	595.2	595.2	599.9	613.9
STANDOVER	762.3	777.5	801.5	832.1