



**DC Sports**  
13000 Temple Ave  
City of Industry Ca, 91746  
T. 626-937-6988  
[www.dcsports.com](http://www.dcsports.com)

---

**AHC6514**  
**HEADER INSTALLATION INSTRUCTIONS**  
**2002-06 ACURA RSX TYPE S**

**\*CARB EXEMPT PER EO# D-370-14\***

**PRE-CARE MAINTENANCE:** To prevent permanent staining of your new DC Sports Header, wipe the header clean with a solution of mild detergent and water. Any contaminants left on the header such as grease, oil, and/or fingerprints will result in PERMANENT staining.

**!!!READ INSTRUCTIONS THROUGH COMPLETELY BEFORE BEGINNING INSTALLATION. FAILURE TO DO SO MAY RESULT IN COSTLY ENGINE AND/OR HEADER DAMAGE!!!**

**\*\*\*FOR YOUR SAFETY, ALLOW ENGINE AND EXHUST SYSTEM TO COOL FOR AT LEAST AN HOUR BEFORE BEGINNING INSTALLATION. \*\*\***

**IF YOU ARE NOT COMFORTABLE AND/OR FAMILIAR WITH THESE INSTRUCTIONS, PLEASE REFER THIS INSTALLATION TO A QUALIFIED PROFESSIONAL.**

1. Utilizing a flat work area (preferably concrete), jack up the front of the car and **support the car on jack stands** under the front jack support points (refer to your owner's manual). **DO NOT USE THE JACK TO SUPPORT THE CAR WHILE WORKING UNDERNEATH!**
2. Unplug the O2 sensor that is closest to the front of the car and un-clip it from the wire support harness.
3. Remove the bolts securing the exhaust manifold to the exhaust secondary, including the bolts that secure the manifold to the support bracket.
4. Loosen the bolt that secures the support bracket to the engine block enough to rotate it out of the way.
5. Remove the rubber hanger from the b-pipe and allow the b-pipe to hang.
6. From the topside of the motor, remove the strut tower bar and the plastic plug wire cover from the valve cover.
7. Remove the two bolts that secure the power steering line to the valve cover.
8. Remove the two nuts and three bolts securing the manifold to the engine.
9. Remove the stock manifold by sliding it off the studs and lifting it out.
10. Carefully remove the donut gasket from the stock manifold and install it on the DC Sports header.
11. Slide the DC Sports header over the studs on the engine and install in reverse order.
12. Make sure to reattach the stock support bracket and to reconnect the O2 sensor plug.
13. **RECHECK ALL YOUR WORK.**
14. Lower the car off the jack stands, start the engine and check for exhaust leaks.  
After approximately 500 miles (800 km) re-check the exhaust system bolts and nuts and retighten as necessary

**PARTS LIST**

Quantity	Part Number	Part Description
1	AHC6514	Ceramic coat 4-2-1 one piece
1	TMTAG-CARBE014	D-370-14 CARB sticker
2	DCDECAL	DC Sports decals

**THANK YOU FOR CHOOSING DC SPORTS**