



13000 Temple Ave. City of Industry, CA 91746

Tech line (626) 968-5147 Main line (800) 237-7560
www.dcsports.com

CAI5513
COLD AIR INTAKE INSTALLATION INSTRUCTIONS
1996-2000 HONDA CIVIC HX, EX 1.6L

**!!! READ ALL INSTRUCTION THOROUGHLY BEFORE BEGINNING
INSTALLATION. FAILURE TO DO SO MAY RESULT IN COSTLY ENGINE
AND/OR SYSTEM DAMAGE!!!**

*****IF UNSURE ABOUT INTAKE SYSTEM INSTALLATION PLEASE HAVE A
REPUTABLE PERFORMANCE SHOP OR A LICENCED MECHANIC
INSTALL THIS SYSTEM*****

*****FOR YOUR SAFETY, ALLOW ENGINE TO COOL FOR AT LEAST AN
HOUR BEFORE BEGINNING INSTALLATION*****

*****PLEASE CHECK AND MAKE SURE ALL HARDWARE IS PRESENT
BEFORE INSTALLATION. PARTS LIST ON LAST PAGE*****

A.R.B INFORMATION

*****THIS DC SPORTS INTAKE ARE CARB EXEMPT
PER EO#D-370-13 FOR 1996-2000 HX EX CIVIC 1.6L ONLY*****

TOOLS REQUIRED

**Ratchet 10mm, and 11mm deep socket
Flat Screwdriver
Phillips Screwdriver**

REMOVAL OF STOCK INTAKE AND INSTALLATION OF INTAKE SYSTEM

1. Loosen the clamp securing the factory intake tube to the throttle body.
2. On the factory intake tube unplug the air temp sensor and all hoses attached to the tube.
3. Locate and remove two 10mm bolts securing the factory air box to the chassis.
4. Unclip the top of the factory air box from the bottom this allows better access to the lower mount.
5. Temporarily slide resonator out, and then slide back air box from mount and remove from vehicle.
6. Remove front bumper by locating seven plastic clips securing the upper section of the bumper cover.
7. Locate and remove two Philips screws securing the bumper to the fender on both fender wells
8. Underneath the bumper in the center locate and remove two 10mm bolts securing the bumper to the chassis.
9. Remove front bumper.
10. Remove the 10mm bolt securing the top of the resonator box on the fender.
11. Locate and remove the 10mm bolt securing the lower section of the resonator box from under the car.
12. Remove the entire resonator box from vehicle by sliding down and out.
13. **WARNING MAKE SURE ENGINE IS COOL BEFORE THESE NEXT STEPS.**

14. On the valve cover remove the crankcase breather hose and remove. Follow down the vacuum/coolant plumbing and remove coolant hoses, and entire vacuum and coolant plumbing from vehicle.
15. With provided 8mm heater hose replace coolant hose that was just removed.
16. Install provided 2.50" coupler and two clamps onto the throttle body but only tighten the clamp towards the throttle body at this time.
17. Loosely install the DC Sports intake tube into the throttle body.
18. Notice the welded bracket on the intake tube. Install provided vibration mount between the bracket and the chassis.
19. Align the bracket on top of the vibration mount and use provided washer and nut to secure the intake tube.
20. Tighten remaining clamp on the throttle body and make sure the pipe is free from any obstructions.
21. Plug air temperature sensor into the grommet on the DC sports intake tube.
22. Install the 10mm vacuum hose onto the intake tube nipple and the other end into the valve cover.
23. Install the DC Sports air filter into the intake tube.
24. Reinstall the bumper cover on reverse order it was removed.
25. Installation is now complete check all work performed

*****LIMITED 10 YEAR WARRANTY*****

DC Sports only warranty's intake systems due to poor workmanship. We do not cover normal wear and tear damages due to misuse or abuse. We do not warranty the finish of intake tubes.

**Warranty covers the original owner of intake system by having proof of purchase.
We have the right to void all warranty if you cannot provide the information needed by DC Sports.
DC Sports does not cover any cost for installation or removal of products.**

*****CAUTION*****

DC Sports does not assume any liability for damage caused by rain or floods causing the intake system for taking on water. We recommend that you remove the cold air intake system due to wet conditions.

*****WARRANTY CLAIMS*****

**All warranty claims must be shipped prepaid by the customer to DC Sports.
Warranty claims must have an RMA (Return Merchandise Authorization) number on the box or package will be refused and sent back to the shipper.**

PARTS LIST

Quantity	Part Number	Part Description
1	DCCAP5513	CAI5513 INTAKE TUBE
1	DCCP250	2.50" STRAIGHT COUPLER
15"	DCHH8MM	8MM HEATER HOSE
12"	DCVH10MM	10MM VACUUM HOSE
2	DCCL250	2.50" CLAMP
1	DCRG58	5/8" RUBBER GROMMET
1	DCSNP58	5/8" SNAP IN PLUG
1	DCVM6MM	M6 M/M VIBRA MOUNT
1	DCF250	2.50" DC SPORTS FILTER PACK
2	DCDECAL	DC SPORTS DECAL

THANK YOU FOR CHOOSING DC SPORTS